QIL CONSERVATION DIVISION -

Page 1 - Revised 10/01/78

This form is not to be used for reporting packer teakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator TENNECO OIL CO				Lease	PAYNE A	Well No. 1E		
location of Well: Un	itN	Sec 19	Tup. 29N	Rge.	10W	County	SAN JUAN	
	NAME OF RESERVOIR OR POOL			TYPE OF PI	TYPE OF PROD. (Oil or Gee)		PROD. MEDIUM (Tog. or Cag.)	
Upper Completion	OTERO CHACRA		GAS	GAS		TUBING		
Lower Completion	BASIN DAKOTA		GAS	GAS F		TUBING		
			PRE-FLO	OW SHUT-IN P	RESSURE DATA			
Hou Upper	ir, date shi	ut-in	Langth of time shu	ıt-ın	SI press. psig		Stabilized? (Yes or No)	
completion: 2;30 pm 4-6-87 72 hours						Yes Stabilized? (Yes or No)		
Lower	ir, date shi 2:30	om 4-6-87	Length of time and 72 hot		i		bilized? (Yes or No) Ves	
		<u> </u>	72 110	FLOW TEST	·	· · · · · · · · · · · · · · · · · · ·		
onmenced at ()	hour, gale	* 11:30	am 4-9-87	12011 1201	Zone producing (Upper or Lower): UDDe'r			
TIME		LAPSED TIME		PRESSURE		F	Y	
9:00 am	•)	SH4CE*	Upper Completion	Lower Completion	TSMP.		REMARKS	
4-10-87	1	21½ hours	440	1000		dakota will not produce.		
10:30 am	ln:30 am		420	1000				
4-11-87		47 hours	421)	נינייניב		logged of	T -	
-								
						- 		
roduction	rate du	ring test					.,	
Oil:		BOP.	D based on	Bbls. ir	n Hour	s G12	v GOR	
Gas:		155	MCF	PD; Tested thru	(Orifice or Mete	er):mete	<u>2</u> r	
			MID-TI	EST SHUT-IN P	RESSURE DATA			
Upper	ur, date sh							
Lower	Hour, date shut-in Length of time shut-in			ut-in	SI press; paig Stabilized? (Yes or No)			
Completion								
					APR	15 1987	IJ	
		ľ			OH OF	100/		
				,	The second secon	14. 011		
				(Continue on t	everse side) 🧢 🦠	DE No. 2€		

FLOW TEST NO. 2

ommenced at (hour, d	ato)中中		Zone producing (Uriper or Lower)			
TIME (hour, date)	LAPSED TIME BINCE # #	PRESSURE		PROD. ZONE	1	EMARKS
		Upper Completion	Lower Completion	TEHT.	·	EMARKS
						ļ
	 					
					-	
Pa						
	<u> </u>		<u> </u>	<u> </u>	1	
roduction rate	during test					•
):I.	F.O.1	D 1 1	D11. '-		C	GOR
G25:		MCF	PD: Tested thru	(Orifice or Mete	r):	
lemailus:						
						<u>-</u>
hereby certify	that the informat	ion herein contain	ned is true and co	omplete to the b	st of my knowledge	: .
t normal		APR 1 5 10	o ₹ 0(TE	NNECO OIL CO	
Approved APR 1 5 19879				Operator	X -	,
2.27. 2.22.20			3	By John	Lucto	JOHN CARTER
Ori	iginal Signed by CH	ARLES GHOLSON				AGENT
Ву				Tide		(A) II. (4.1
Title	EPUTY OIL & GAS	inspector, dist. #3	3	Date4	13-87	
				UEK		

NORTHWEST NEW MEDICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packet or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operator shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such ten shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage tent, a gas well it being flowed to the autosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Ten No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut in while the zone which was previously shut in is produced.
- 7. Fressures for gavizone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours ests unmediately prior to the beginning of each flow-period, at fifteen-minute interval during the first hour thereof, and at hours intervals thereafter, including one pressure neasurement immediately prior to the conclusion of each flow period, 3 dear one time during each flow period (2) approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauses the accuracy of which must be the held at least twice, once at the beginning and once at the end of each test, with deadwarpht pressure gause. If a well is a gas-oil or in oil-gas dual completion, the recording gause shall be required on the oil gone only, with deadweight pressures as required above being taken on the gas zone.

E. The results of the above-described term shall be filed in triplicate within 13 days after completion of the test. Term shall be filed with the Aster District Office of the New Messon Oil Conservation Division on Northwest New Messon Packer Leakage Test Form Revised 10-01-7E with all desidweight pressures indicated thereon as well as the flowing emperatures (gas zones only) and gravity and GCR (oil zones only).