STATE OF NEW MEXICO INERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Derator: AMOCO PRODUCTION COMPANY Lease/Well #:PAYNE A 001E CMGLD

erat Met	er #:02885		0-000-00			THOD PRO		DIUM PROD	
	NAME RESER	WOIR OR POOL		TYPE PROD	MET	HOD PRO			
PR MP	PAYNE A 001	LE MV/CH COMG	02885	Bas	bas FI			TBE	
R MP		1E DK 93665							
	Lower zone	YS TO A PRE-FLOW	SHUT-IN	PRESSURE DA	ATA				
	Hour/Date			e Shut-In		Press.	PSIG	Stabilzed	
R MP,	02/13/92		72 Hours			438		No	
VR OMP	11:04 AM 02/13/92		72 Hours			478		Yes	
	.		FLOW TEST	DATE NO.1	.			- I /	
mme	enced at (ho	our,date)*				Zone P		ng (Upr/Lwr	
		LAPSED TIME	RESSURE	Prod Lower Temp.					
TIME (hour, date) 03/13/92 03/14/92		SINCE*	Upper				REMARKS		
		Day 1	Tub 363 Cas 481	478		4977 30 50 50 50 50		Both Zones SI Both Zones SI	
		Day 2		481					
02/15/92		Day 3	TUB 481	479		·		Both Zones SI	
03/16/92		Day 4	TUB 438	478			- Tornet	on upper zere	
02/17/92		Day 5	Tub 178	477	477				
07/18/92		Day 6	Tub 176	477					
rod	uction rate	during test BOPD base	a		ice	Hrs	Gr r):MET	eav GOR	
Gas:				-IN PRESSUR		ATA		anna on the State	
UPR COMF		e SI Length	of Time S	SI Pres	s. I	PSIG		2 eta (yes/no 0 1352	
LWR	_				<u>,,</u>		OIL C	M. DIV.)	
			ontinue o	n reverse s	side	<u> </u>			

FLOW TEST NO. 2

mmenced at (nour, o	810) T T		Zone producing (Upper or Lower):				
TIME	LAPSED TIME	PRESSURE		PROD. ZOME			
(hour, date)	SINCE **	Upper Completion	Lower Completion	TEMP.	REM	ARKS	
	1		1				
···							
		Ì				•	
	<u> </u>						
		1					
			 				
	İ						
	·						
			i				
		<u>l </u>		<u> </u>	:		
				(Orifice or Meter)):	- 	
narks:							
			··				
reby certify	that the informat	ion herein contair	ned is true and co	implete to the bes	t o£mv knowledge	▲	
ereby certify	that the informat	ion herein contair	ned is true and co	omplete to the bes	t of my knowledge.	0. , _e.	
proved	MAR 1 (15)	<u>.2</u>	19 (Operator	Imoco (roduction	
proved	that the information of the second of the se	<u>.2</u>	19 (Operator	Imoco (roduction	
proved	MAR 1 (15)	<u>.2</u>	19 (Operator	Imoco (roduction	
provedN	Dil Conservation	Division	19 (Operator	Imoco (roduction	
provedN	MAR 1 (15)	Division		Operator By Title	san Wood	Production les rech	
Proved Nexico C	Dil Conservation	Division		Operator	san Wood	roduction	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a desidweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).