

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator CARIBOU FOUR CORNERS, INC.		8. Farm or Lease Name KIRTLAND
3. Address of Operator Rm 219 Transwestern Bldg. Billings, Mont. 59101		9. Well No. #7
4. Location of Well UNIT LETTER <u>D</u> , <u>910</u> FEET FROM THE <u>NORTH</u> LINE AND <u>395</u> FEET FROM THE <u>WEST</u> LINE, SECTION <u>13</u> TOWNSHIP <u>29 N</u> RANGE <u>15 W</u> NMPM.		10. Field and Pool, or Wildcat CHA CHA GALLUP
15. Elevation (Show whether DF, RT, GR, etc.) 5127 GL, 5141 KB		12. County SAN JUAN

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:


PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-21-80 Spudded with cable tools at 5:00 p.m.
9-29-80 TD 343' with cable tool. Ran 8 jts. 8 5/8" 23# measuring 338.0', set at 339 GL. Set with 275 sacks cement, 3% CaCl₂ and 1/4# floseal per sack. Good returns throughout, circulated 25 sacks cement to the pit.
10-11-80 Drilled out from under surface casing at 5:00 p.m.
10-19-80 TD 4722 at 7:15 p.m.
10-20-80 Ran Schlumberger logs.
10-21-80 Ran 123 jts. 9.5# and 10.5# 4 1/2" casing. Cemented with 1025 sacks in two stages. Did not circulate cement to surface. Stage tool set at 3407 KB.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Denny G. Forst TITLE Geologist DATE 11-13-80

Original Signed by FRANK T. CHAVEZ

SUPERVISOR DISTRICT # 3

NOV 17 1980

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: