

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name Ransom
9. Well No. 1 M
10. Field and Pool, or Wildcat Aztec - P. C.
12. County San Juan

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-
2. Name of Operator Manana Gas, Inc. (505) 325-3066
3. Address of Operator P. O. Box 145 Farmington, NM 87401
4. Location of Well UNIT LETTER <u>O</u> , <u>1240</u> FEET FROM THE <u>South</u> LINE AND <u>2435</u> FEET FROM THE <u>East</u> LINE, SECTION <u>13</u> TOWNSHIP <u>29N</u> RANGE <u>11W</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 5581 G

16.

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

### NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

### SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>


17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud 12/3/80.

Ran 7 5/8" surface casing to 122' cemented w/65 sx, cement circulated to surface.

TD 1938'

Ran 2 7/8" production casing to 1937' cemented w/125 sx low dense and 125 sx of neat cement for a total of 250 sx. Cement circulated to surface. Let stand overnight - no water loss.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED FRANK T. CHAVEZ TITLE Vice President DATE 12/10/80

Original Signed by FRANK T. CHAVEZ

SUPERVISOR DISTRICT 8

DEC 12 1980

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: