STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

Location of Well: P252910 Page 1

OIL CONSERVATION DIVISION NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator: AMOCO PRODUCTION COMPANY Lease/Well #:LEFKOVITZ GC B 1E
Meter #:94410 RTU:1-236-03 County:SAN JUAN

Meter #:94410		RTU	1:1-236-03	County:SAN JUAN			
	NAME RESERVOIR OR P			TYPE PROD	METHOD PROI	MEDIUM PROD	
UPR COMP	LEFKOVITZ	GC B 1E MV 944	11 عردد	GAS	FLOW	TBG	
LWR COMP	LEFKOVITZ	GC B 1E DK 944	110 2-160-3	GAS	FLOW	TBG	
		PRE-FLO	W SHUT-IN	PRESSURE DA	ATA		
	Hour/Date Shut-In		Length of Time Shut-In		SI Press PSIG Stabilzed		
UPR COMP	09/27/93					00121.833	
LWR COMP	09/27/93			OIL CONTROL OF CONTROL			
			FLOW TEST	DATE NO.1		•••	
Comme	nced at (ho	our,date)*			Zone Pro	oducing (Upr Lwr)	
TIME (hour, date)		LAPSED TIME SINCE*	PR Upper	ESSURE Lower	Prod Temp.	REMARKS	
0	9/27/93	Day 1	274	273		Both Zones SI	
09/28/93		Day 2	335	293		Both Zones SI	
09/29/93		Day 3	337	301		Both Zones SI	
09/30/93		Day 4	338	302			
/	0/013/93	Day 5	340	282			
10/02/93		Day 6	342	268			
Produ Oil:_ Gas:	ction rate	MFC	d on	heu (Orific	ce or Meter)	GravGOR :METER	
UPR COMP	Hour, Date	e SI Length	of Time SI	SI Press	. PSIG Stal	pilized (yes/no)	
LWR COMP							
	- 1 	(C	ontinue on	reverse sid	de)		

FLOW TEST NO. 2

nmenced at thour, de	1(e) 平 平		Zone producing (Up;	per or Lewer):	
TIME	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE	
(hour, date)		Upper Completion	Lewer Completion	TEMP.	REMARKS
					·
	 				
		<u> </u>			
•					
	·				
	J	<u> </u>	<u> </u>	<u> </u>	(
oduction rate d	-	D based on	Bhls in	Hours	Grav GOR
as:		MCF	PD: Tested thru	(Orifice or Meter):
Cinaras.		7 11 11 11			
		· · · · · · · · · · · · · · · · · · ·			
h					
					t of my knowledge.
pproved	061 2 1	1993	19 C	perator	Amoco Goduction Comp
New Mexico O	il Conservation I	Division			
			B	by	san (lovda)
7 	J. Karly Co	gay varanga	Т	ide Jil	ld Technologist
ide <u>DEPUTY O</u>	N & GAS INSPEC	TOR DIST #3			-18-93

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).