¥

EE0:17:1992

FARMINGTOL TLAIRICT 5MM

5. LEASE

SF 080724-A

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS  (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
1. oil	2achry 9. WELL NO.
2. NAME OF OPERATOR	30
Union Texas Petroleum Corporation	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Armenta Gallup
P.O. Box 808, Farmington, New Mexico 87499	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	Sec. 33, T29N, R10W, N.M.P.M.  12. COUNTY OR PARISH 13. STATE
AT SURFACE: 860 ft./N; 570 ft./E line AT TOP PROD. INTERVAL: Same as above	San Juan New Mexico
AT TOTAL DEPTH: Same as above	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	24. AT 110.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
	5635 R.K.B.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	The state of the s
SHOOT OR ACIDIZE REPAIR WELL	FD 1
SHOOT OR ACIDIZE REPAIR WELL RECEIVE	(NOTE: Report results of multiple completion or zone
	change on Form 9–330.)
MULTIPLE COMPLETE DEC 10 190	)L
CHANGE ZONES	
ABANDON*  (other) Ran 5-1/2" Casing as Liner X  (other) Ran 5-1/2" Casing as Liner X  FARMINGTON N.	SURVEY M
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is different measured and true vertical depths for all markers and zones pertinent	Rectionally diffied, kive appartiace locations and
1. Drilled 6-3/4" hole with gas to total depth of reached on 12/5/82.	
2. Ran 19 joints of 5-1/2", 15.50#, K-55 casing at 5958 ft. R.K.B. Top of liner was set at 5	as a liner. Bottom of liner was set 5154 ft. R.K.B.
3. Cemented with 210 cu. ft. of 50-50 Pozmix with Flocele per sack, and 10 lb. of salt per sack.	k. Plug down at 11:15 A.M. 12/6/82.
4. Reversed out about 16 bbls. of cement slurry	from liner cop.
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED Kenneth E. Roddy TITLE Area Prod. St	ipt. Date December 8, 1982
(This space for Federal or State off	ice use)
B F 6	CO C DATE
APPROVED BY TITLE	100 27 200
	MPOSE IS A SELECTION UPOSE IS A SESONAL
UEU	

\*See Instruction Offerense Set DIV.