

SANTA FE, NEW MEXICO 87501

DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)1. OIL ☐ WELL GAS ☒ WELL OTHER-
2. Name of Operator

Amoco Production Company

3. Address of Operator
501 Airport Dr., Farmington, NM 87401

4. Location of Well

UNIT LETTER I 1615 FEET FROM THE South LINE AND 1115 FEET FROM
THE East LINE, SECTION 29 TOWNSHIP 29N RANGE 10W NMPM.

7. Unit Agreement Name

8. Farm or Lease Name
Abrams J9. Well No.
110. Field and Pool or Wildcat
Armenta Gallup/
Bloomfield Chacra Ext.

15. Elevation (Show whether DF, RT, GR, etc.)

5535' GL

12. County
San Juan16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:PERFORM REMEDIAL WORK ☐TEMPORARILY ABANDON ☐PULL OR ALTER CASING ☐PLUG AND ABANDON ☐CHANGE PLANS ☐OTHER ☐REMEDIAL WORK ☐COMMENCE DRILLING OPNS. ☐CASING TEST AND CEMENT JOB ☐OTHER ☐ALTERING CASING ☐PLUG AND ABANDONMENT ☐Spud and Set Casing ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Amoco Production Company spudded a 17-1/2" hole on 12-6-82 and drilled to 322'. Set 13-3/8" surface casing at 315' on 12-9-82 and cemented with 743 cu ft class B cement containing 2% CaCl₂. Circulated good cement to surface. Drilled a 12-1/4" hole to 3454' and set 9-5/8" casing at 3454', and cemented with 1232 cu ft class B 50:50 poz, 6% gel, 2# med. tuf plug, and .8% FLA. Tailed in with 590 cu ft class B neat cement, and circulated good cement to surface. Drilled a 8-1/2" hole to 5304' and set a 7" liner at 5304' and cemented with 539 cu ft class B 50:50 poz, 6% gel, 2# med tuf plug, and .8% FLA. Tailed in with 118 cu ft class B neat cement. Drilled a 6-1/4" hole to a TD of 5778' which was reached on 12-30-82, and set a 4-1/2" liner at a depth of 5763' and cemented with 177 cu ft class B neat cement to 5135'. Released the rig on 12-31-82.

TOL

RECEIVED
APR 18 1983
CIVIL DIV.
SANTA FE

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original Signed by
D.D. Lawson

SIGNED

TITLE Dist. Admin. Supvr.

DATE 4-14-83

APPROVED BY

Original Signed by FRANK T. CHAVEZ

TITLE SUPERVISOR DISTRICT # 3

DATE

APR 18 1983

CONDITIONS OF APPROVAL, IF ANY: