

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE\*  
(Other instructions on re-  
verse side)

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

SF-078578A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

UNIT AGREEMENT NAME

7. NAME OF LEASE NAME

Howell K

9. WELL NO.

302

10. FIELD AND POOL, OR WILDCAT

Undes.Fruitland Coal

11. SEC., T., R., M., OR B.L. AND  
SURVEY OR AREA

Sec.22,T-30-N,R-08-W  
N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan

NM

1. OIL WELL ☐ GAS WELL ☐ X OTHER

2. NAME OF OPERATOR

Meridian Oil Inc.

3. ADDRESS OF OPERATOR

Post Office Box 4289, Farmington, NM 87499

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface 2056'N, 1675'W

14. PERMIT NO.

15. ELEVATIONS (Show whether DP, RT, GR, etc.)

5832'GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PEEL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Spud Well

(Note: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DRY HIDE PRODUCED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

09-07-88 Spudded well at 1:30 pm 09-07-88. Drilled to 230'. Ran 5 jts. 9 5/8", 36.0#, K-55 surface casing set at 230'. Cemented with 150 sks. Class "B" with 1/4#/sk. gel-flake and 3% calcium chloride (160 cu.ft.). Circulated to surface. WOC 12 hrs. Tested 600#/30 minutes, held ok.

09-09-88 TD 2469'. Ran 57 jts. 7", 20.0#, K-55 intermediate casing, 2456' set @ 2469'. Cemented with 350 sks. Class "B" 65/35 Poz, with 6% gel, 2% calcium chloride and 1/2 cu.ft./sack perlite (673 cu.ft.) followed by 100 sks. Class "B" with 2% calcium chloride (118 cu.ft.). WOC 12 hours. Held 1200#/30 min.

RECEIVED

SEP 13 1988

OIL CON. DIV

DIST 2

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Regulatory Affairs

DATE

09-12-88

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMOC

\*See Instructions on Reverse Side