## Submit 3 Copies to Appropriate District Office

## State of New Mexico Energy, Minerals and Natural Resources Department

Form	C	-1(	13	
Revis	ed	1.	1-8	3

.O. Box 1980, Hobbs, NM 88240	WELL API NO.
P.O. Box 2088  ISTRICT II Santa Fe New Mexico, 87504-20	30-045-28118
O. Drawer DD, Artesia, NM 88210  Santa Fe, New Mexico 87504-20	5. Indicate Type of Lease
STRICT III OO Rio Brazos Rd., Azzec, Nivi 87410	STATE X FEE  6. State Oil & Gas Lease No.
	6. State Oil & Gas Lease No. E5462-4
SUNDRY NOTICES AND REPORTS ON WELLS	
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	7. Lease Name or Unit Agreement Name
Type of Weilt OIL CAS WELL X OTHER	Gallegos Canyon Unit
Name of Operator BHP Petroleum (Americas), Inc.	8. Well No. 397
Address of Operator	9. Pool name or Wildcat
5847 San Felipe, Suite 3600 Houston, TX 77057	Basin Fruitland Coal
Well Location  Unit Letter K: 1555 Feet From The South Line	and 1965 Feet From The West Line
Section 36 Township 29N Range 13	
10. Elevation (Show whether DF, RKB, RI	T. GR, etc.)
Check Appropriate Poy to Indicate Nature of	Wester Reserve of Other D
Check Appropriate Box to Indicate Nature of NOTICE OF INTENTION TO:	
	SUBSEQUENT REPORT OF:
	AL WORK ALTERING CASING
MONT 2 1220	NCE DRILLING OPNS. PLUG AND ABANDONMENT
O'I CON DIV.	TEST AND CEMENT JOB
HER: DIST. 3	Well History X
Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinwork) SEE RULE 1103.	uent dates, including estimated date of starting any proposed
Spud well @ 6:30 PM on 10/29/90. Drld 8-3/4" h	1 . 1001 *** 7
J-55 8R ST&C csg and landed @ 133' KB. Cmt w/l sx Cello-seal, obtained full returns w/8 bbl cm Test csg & blind rams to 2,000 psi. Drld 6-1/4 Ran DIL/GR/SDL/DSN/Coal logs. Ran 35 jts 4-1/2 @ 1432' KB. Cmt w/195 sxs lead 50/50 POZ w/2% tail in w/30 sxs Class "B" w/l.2% CFl8. Obtain to surface. Released rig @ 7:00 AM 11/1/90.  NOTE: 7" csg cmt'd w/118 cu ft cmt. 4-1/2" csg cmt'd w/246 cu ft lead follow	00 sxs Class "B" w/2% CaCl, 1/4# at circ to surface. WOC & NU BOP. "hole from 138' to 1448'. POOH. "10.5# 8R J-55 ST&C csg & landed gel, 10% salt, 1/4# sx Cello-seal, and full returns w/11 bbls cmt circ
J-55 8R ST&C csg and landed @ 133' KB. Cmt w/l sx Cello-seal, obtained full returns w/8 bbl cm Test csg & blind rams to 2,000 psi. Drld 6-1/4 Ran DIL/GR/SDL/DSN/Coal logs. Ran 35 jts 4-1/2 @ 1432' KB. Cmt w/195 sxs lead 50/50 POZ w/2% tail in w/30 sxs Class "B" w/l.2% CFl8. Obtain to surface. Released rig @ 7:00 AM l1/1/90.  NOTE: 7" csg cmt'd w/l18 cu ft cmt. 4-1/2" csg cmt'd w/246 cu ft lead follow	00 sxs Class "B" w/2% CaCl, 1/4# at circ to surface. WOC & NU BOP. "hole from 138' to 1448'. POOH. "10.5# 8R J-55 ST&C csg & landed gel, 10% salt, 1/4# sx Cello-seal, and full returns w/11 bbls cmt circ
J-55 8R ST&C csg and landed @ 133' KB. Cmt w/l sx Cello-seal, obtained full returns w/8 bbl cm Test csg & blind rams to 2,000 psi. Drld 6-1/4 Ran DIL/GR/SDL/DSN/Coal logs. Ran 35 jts 4-1/2 @ 1432' KB. Cmt w/195 sxs lead 50/50 POZ w/2% tail in w/30 sxs Class "B" w/l.2% CFl8. Obtain to surface. Released rig @ 7:00 AM 11/1/90.  NOTE: 7" csg cmt'd w/118 cu ft cmt. 4-1/2" csg cmt'd w/246 cu ft lead follow	00 sxs Class "B" w/2% CaCl, 1/4# at circ to surface. WOC & NU BOP. "hole from 138' to 1448'. POOH. "10.5# 8R J-55 ST&C csg & landed gel, 10% salt, 1/4# sx Cello-seal, ed full returns w/11 bbls cmt circ
J-55 8R ST&C csg and landed @ 133' KB. Cmt w/l sx Cello-seal, obtained full returns w/8 bbl cm Test csg & blind rams to 2,000 psi. Drld 6-1/4 Ran DIL/GR/SDL/DSN/Coal logs. Ran 35 jts 4-1/2 @ 1432' KB. Cmt w/195 sxs lead 50/50 POZ w/2% tail in w/30 sxs Class "B" w/l.2% CFl8. Obtain to surface. Released rig @ 7:00 AM l1/1/90.  NOTE: 7" csg cmt'd w/l18 cu ft cmt. 4-1/2" csg cmt'd w/246 cu ft lead follow dereby cerufy that the information above is true and complete to the best of my knowledge and belief.  ONATURE Productive Company	OO sxs Class "B" w/2% CaCl, 1/4# at circ to surface. WOC & NU BOP. "hole from 138' to 1448'. POOH. "10.5# 8R J-55 ST&C csg & landed gel, 10% salt, 1/4# sx Cello-seal, and full returns w/11 bbls cmt circ  red by 35 cu ft tail.
J-55 8R ST&C csg and landed @ 133' KB. Cmt w/l sx Cello-seal, obtained full returns w/8 bbl cm Test csg & blind rams to 2,000 psi. Drld 6-1/4 Ran DIL/GR/SDL/DSN/Coal logs. Ran 35 jts 4-1/2 @ 1432' KB. Cmt w/195 sxs lead 50/50 POZ w/2% tail in w/30 sxs Class "B" w/1.2% CFl8. Obtain to surface. Released rig @ 7:00 AM 11/1/90.  NOTE: 7" csg cmt'd w/118 cu ft cmt. 4-1/2" csg cmt'd w/246 cu ft lead follow	OO sxs Class "B" w/2% CaCl, 1/4# at circ to surface. WOC & NU BOP. "hole from 138' to 1448'. POOH. "10.5# 8R J-55 ST&C csg & landed gel, 10% salt, 1/4# sx Cello-seal, and full returns w/11 bbls cmt circ  red by 35 cu ft tail.
J-55 8R ST&C csg and landed @ 133' KB. Cmt w/l sx Cello-seal, obtained full returns w/8 bbl cm Test csg & blind rams to 2,000 psi. Drld 6-1/4 Ran DIL/GR/SDL/DSN/Coal logs. Ran 35 jts 4-1/2 @ 1432' KB. Cmt w/195 sxs lead 50/50 POZ w/2% tail in w/30 sxs Class "B" w/l.2% CFl8. Obtain to surface. Released rig @ 7:00 AM l1/1/90.  NOTE: 7" csg cmt'd w/l18 cu ft cmt. 4-1/2" csg cmt'd w/246 cu ft lead follow Beverly Comer THEOR PRINT NAME  THEOR PRINT NAME  THE Product of the best of my knowledge and belief.  Product of the product of the best of my knowledge and belief.	OO sxs Class "B" w/2% CaCl, 1/4# at circ to surface. WOC & NU BOP. "hole from 138' to 1448'. POOH. "10.5# 8R J-55 ST&C csg & landed gel, 10% salt, 1/4# sx Cello-seal, and full returns w/11 bbls cmt circ  ed by 35 cu ft tail.  DATE 11/6/90  TELEPHONE NO. 713-780-5
J-55 8R ST&C csg and landed @ 133' KB. Cmt w/l sx Cello-seal, obtained full returns w/8 bbl cm Test csg & blind rams to 2,000 psi. Drld 6-1/4 Ran DIL/GR/SDL/DSN/Coal logs. Ran 35 jts 4-1/2 @ 1432' KB. Cmt w/195 sxs lead 50/50 POZ w/2% tail in w/30 sxs Class "B" w/l.2% CFl8. Obtain to surface. Released rig @ 7:00 AM l1/1/90.  NOTE: 7" csg cmt'd w/l18 cu ft cmt. 4-1/2" csg cmt'd w/246 cu ft lead follow Beverly Comer  THE Production above is true and complete to the best of my knowledge and belief.  Production of the product of the best of the	00 sxs Class "B" w/2% CaCl, 1/4# at circ to surface. WOC & NU BOP. "hole from 138' to 1448'. POOH. "10.5# 8R J-55 ST&C csg & landed gel, 10% salt, 1/4# sx Cello-seal, ed full returns w/11 bbls cmt circ  ed by 35 cu ft tail.