

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill, or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

Name of Operator

Hardson Operating Company

Address and Telephone No.

00 Lincoln, Suite 1700, Denver, Colorado 80203 (303) 830-8000

Location of Well (Footage, T, R, M, or Survey Description)

40' FSL & 1320' FWL

c. 25-T29N-R14W

5. Lease Designation and Serial No.

14-20-603-2172

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Navajo 25-1

9. API Well No.

30-045-30041

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal/W Kutz PC ext.

11. County or Parish, State

San Juan County, NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
☐ Notice of Intent	☐ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment Notice	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☐ Surface Casing/Cementing
	☒ Other: see below
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut-Off
	☐ Conversion to Injection
	☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markets and zones pertinent to this work.)

22-01 Spud 8 5/8" surface hole. Drill to 135'. Ran 3 jts 7" 20# casing and set at 135'. Cemented with 30 sxs Class "B" Neat cement with 1/4# celloflake and 3% CaCl₂. Circulated 3 bbls cement to surface.

23-01 Test BOP and casing to 2000#

24-01 Drill to 1340' KB. Secure Location

25-01 TD Well @ 1640'. Circulate well clean-SDFN

26-01 Run 40 jts 4 1/2" 9.5# casing to 1618.5KB'. Cemented with 80 sxs Class B cement w/ 2% metasilicate and 10 sxs Class B w/ 2% CaCl₂. Displaced plug w/25 BBLs H₂O Circulated 3 bbls cement to surface. RDMOL

I hereby certify that the foregoing is true and correct.

Signed: *[Signature]* Title: Operations Manager

Date: Jan 23, 2002

(This space for Federal or State office use)

Approved by:

Title: Date:

Conditions of approval, if any:

The 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instructions on Reverse Side

NMOCD