

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

DISTRICT I

P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.

30-045-30070

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Morris Gas Com

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

Cross Timbers Operating Company

3. Address of Operator

2700 Farmington Ave., Bldg. K. Ste 1 Farmington, NM 87401

8. Well No.

#1R

9. Pool name or Wildcat

Aztec Pictured Cliffs

4. Well Location

Unit Letter M : 885 Feet From The South Line and 1,240 Feet From The West Line

Section 26 Township 29N Range 10W NMPM San Juan County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

5,537' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Please see the enclosed copy of the drilling report for the above mentioned well.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Drilling Engineer

DATE 5/25/00

TYPE OR PRINT NAME JW Patton

TELEPHONE NO. 324-1090

(This space for State Use)

ORIGINAL SIGNED BY CHARLES T. PERREN

DEPUTY OIL & GAS INSPECTOR, DIST. 3

MAY 31 2000

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Morris Gas Com #1R

5/17/00 Spudded well @ 10:00 a.m. (5/16/00). Drld 8-3/4" hole to 60' Hit boulders.

5/18/00 Drld thru boulders to 215'. Ran 5 jts 7", 20.0# csg. Cmt'd csg w/110 sx cl "B" cmt. Circ 7 bbls cmt to surface. WOC.

5/19/00 Drlg ahead @ 709'.

5/20/00 Drlg ahead @ 1,208'.

5/21/00 Drlg ahead @ 1,800'.

5/22/00 Reached TD @ 2,100'. Short tripped bit. Hole Tight. Washed to bottom.

5/23/00 Ran new 4-1/2" csg to 2,102' KB. Cmt'd csg w/250 sx Prmium Lite HS (65% Type III cmt, 35% poz, 6% gel 10#/sx CSE) w/2% CaCl₂ & 1/4#/sx cellofloake mixed @ 12.5 ppg & 2.07 cuft/sx. Circ 15 bbls cmt to surface. Bumped plug. Float held OK. Pressure tested csg to 1,500 psig. Csg held OK. Installed wellhead. RDMO drlg rig. Released rig @ 8:00 p.m.