

DISTRICT I

P.O. Box 1980, Hobbs NM 88241-1980

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

WELL API NO.

30-045-30071

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

Cross Timbers Operating Company

8. Well No.

#1R

3. Address of Operator

2700 Farmington Ave., Bldg. K. Ste 1 Farmington, NM 87401

9. Lease Name or Unit Agreement Name

Trujillo Gas Com

4. Well Location

Unit Letter K : 1835 Feet From The South Line and 1910 Feet From The West Line

Section 21 Township 29N Range 10W NMPM San Juan County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

5570' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7/28/00 MIRU Drilling Rig. Spudded 8-3/4" hole @ 9:00 a.m. (7/27/00). Started drilling surf hole.

7/29/00 Finished drilling surf hole to 220'. Ran 5 jts 7" surf casing to 213' KB. Cemented surf casing with 95 sx cl "B" cement (15.6 ppg. 1.18 cuft). Circ 7 bbls cement to surface. WOC. SD for weekend.

8/1/00 Installed and pressure tested BOP stack to 250/1,000 psig. Held OK. Drilled out cement. Resumed drilling 6-1/4" hole.

8/11/00 Reached TD of 6-1/4" hole @ 2,005' KB (3:15 a.m. 8/11/00).

8/12/00 Ran 49 jts 4-1/2". 10.5# casing to 1,998' KB. Cement casing with 312 sx Premium Lite cmt (13.5 ppg. 1.64 cuft). Circ 30 bbls cement to surface. Installed wellhead. Released Rig.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE JW Patton TITLE Drilling Engineer DATE 8/21/00

TYPE OR PRINT NAME JW Patton TELEPHONE NO. 324-1090

(This space for State Use) **ORIGINAL SIGNED BY CHARLIE T. PERREN**

DEPUTY OIL & GAS INSPECTOR, DIST. III **AUG 30 2000**

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: