

160-5
(1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill, or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE

FEB 2002

FORM APPROVED

Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No.

SF-079968

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Ropco 9-1

9. API Well No.

30-045-30383

10. Field and Pool, or Exploratory Area

Twin Mounds PC/Basin FC

11. County or Parish, State

San Juan County, NM

Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

Name of Operator

Hardson Operating Company

Address and Telephone No.

30 Lincoln, Suite 1700, Denver, Colorado 80203 (303) 830-8000

Location of Well (Footage, T, R, M, or Survey Description)

FNL, 860' FEL

9-T29N-R14W

CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Surface Casing/Cementing
☒ Other: see below

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well

Completion or Recompletion Report and Log form).

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.

well is directionally drilled, give subsurface locations and measured and true vertical depths for all markets and zones pertinent to this work.)

/01 Spud 8 3/4" surface hole. Drill to 135'.

/01 Drill to 135'. Ran 3 jts 7" 20# casing and set at 131'. Cemented with 50 sacks of Class "B" with 2% KCL. Circulated 4.5 bbls to surface. WOC 12 Hours

6/01 Install BOP, Pressure test, good, TIH w/ 6 1/4" bit. Tag CMT @ 118. Cont. drilling to 750'.

/01 Drill to 1050' OHTD, Circulate hole clean. MIRU San Juan Casing, run 25 jts 4 1/2" 10.5# J-55 casing shoe set @ 1039.62' KB. Circulate hole w/ 105% drill fluid-MIRU American Energy-pump 10 BBLs H2O, Pump 25 sacks 2% Met 1/4" Cello-pump 109 Sx 1/4" Cello 16 BBLs Displacement H2O, 5 BBLs CMT to pit. Good returns. Rdown.

I hereby certify that the foregoing is true and correct.

Signed:

Title: Operations Manager

Date: January 23, 2002

(This space for Federal or State office use)

Received by:

Title:

Date:

Signature of approval, if any:

8 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent

statements or representations as to any matter within its jurisdiction.

* See Instructions on Reverse Side

NMOOD

Handwritten signature