

Form 9-331a
(Feb. 1961)


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. SP 078580-A

Unit N/2 of Sec. 5



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)


Well No. L. F. Moore is located 225 ft. from [N] line and 850 ft. from [E] line of sec. 5
N/4 Sec. 5 (1/4 Sec. and Sec. No.) 30N (Twp.) 8W (Range) 107W (Meridian)
Blanco (Manuelito) (Field) Santa Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 6271 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Ran 99 joints (3231') of 7 5/8" 26-lb 4-55 SS casing. Landed at 3241. Cemented with 150 sacks. Casing was pressured to 800 for 1 hour with no drop in pressure, after cement set, plug was drilled and hole blown dry with gas. It remained dry and drilling ahead with gas was resumed.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Dalby-Saylor Oil Corporation

Address P. O. Box 1175

Farmington, New Mexico

By [Signature]

Title Dist. Supt.

