For ()	<b>m 9-</b> Feb. 1	• <b>831 a</b> 951)	

## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Land Office	Sent	a Pe	
Lease No	1777 CH		
<sub>Unit</sub> San	Juan	3 <b>1-</b> 6	Unit
14-	08-00 <b>1</b> -	464	

**00** 

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT.
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHECK MA	RK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	July 18 , 19 59
	(Range) (Meridian)  Rio Arriba New Mexico ty or Subdivision) (State or Territory)  level is 6500 ft.
DETA	AILS OF WORK
tate names of and expected depths to objective sands; show ing points, and al	AILS OF WORK sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ll other important proposed work)
tate names of and expected depths to objective sands; show ing points, and al 7-12-59 TotalDepth 7743'.  12 joints 7", 26.00#, N-CO casing 57') and 123 joints 7", 23.00#, J-23') set at 7736'. Cemented with	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-ll other important proposed work)  (397) and 99 joints 7°, 23.00%, N-80 casing 55 casing (5052', for a total of 190 joints 640 sacks regular cement, no Tuf-plug/sk., 0.4% HR.
tate names of and expected depths to objective sands; show ing points, and all [-12-59 TotalDepth 7743'.  12 joints 7", 26.00#, N-60 casing 7') and 123 joints 7", 23.00#, J-23') set at 7736'. Cemented with a 2# Gel, 1/4# Flocele/sk, 1/2# Fix Neat cement.  1 1000#/30 minutes.  of cement by temperature survey at 1 understand that this plan of work must receive approval ompany. El Fasc Natural Gas Company.	sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work)  (357) and 95 joints 7°, 23.00°, N-80 casing 55 casing (5052', for a total of 190 joints 640 sacks formix, 640 sacks regular cement, ne Tuf-plug/sk., 0.4% HR. Colored by 50  t 2400'.
tate names of and expected depths to objective sands; show ing points, and all 7-12-59 Total Depth 7743'.  12 joints 7", 26.00#, N-60 casing 57') and 123 joints 7", 23.00#, J-23') set at 7736'. Cemented with a 2% Gel, 1/4# Plocele/sk, 1/2# Fix Neat cement.  1 1000#/30 minutes.  of cement by temperature survey at	sizes, weights, and lengths of proposed casings; indicate mudding jobs, comental other important proposed work)  (357) and 95 joints 7, 23.00f, N-80 casing 55 casing (5052', for a total of 190 joints 640 sacks formix, 640 sacks regular cement, no Tuf-plug/sk., 0.4% HR. of load by 50 commenced.