

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

October 7, 1954

(Date)

Durango, Colorado

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Blackwood & Nichols Company

(Company or Operator)

Northeast Blanco Unit (E-505-6)

(Lease)

Fleeger-Riley Drilling Company

(Contractor)

Well No. 21-36 in the SE 1/4 SW 1/4 of Sec. 36

T. 31N, R. 7W, NMPM, Blanco Mesaverte Pool, Rio Arriba County.

The Dates of this work were as follows: August 30-September 2, 1954 and September 23-25, 1954

Notice of intention to do the work (was) ~~received~~ submitted on Form C-102 on August 13, 1954,
(Cross out incorrect words)and approval of the proposed plan (was) ~~received~~ obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Spudded at 2:00 AM 8-30-54.

On 8-31-54, ran 7 Jts 10-3/4" 32.75# H40 casing - 221' set at 233'. Cemented with 200 sx Ideal regular cement. Cement circulated. On 9-2-54 tested 10-3/4" casing with 800 PSI for 30 minutes before and for 15 minutes after drilling plug & guide shoe. Held OK.

On 9-23-54, ran 175 Jts 7" 23# & 20# J55 casing - 5334' set at 5344'. Cemented with 175 sx 4% gal mixed with 44 sx Strata-Crete, followed with 75 sx neat cement. Temperature survey shows top of cement at 4205'. On 9-25-54, tested casing with 1000 PSI for 30 minutes. Held OK. Drilled cement & float shoe with gas. No water.

Witnessed by Harvey E. Vanderalice

(Name)

Blackwood & Nichols Co.

(Company)

Petroleum Engineer

(Title)

Approved:

OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name De Lasso Loos DE LASSO LOOS

Position Field Superintendent


Representing Blackwood & Nichols Company

Address P.O. Box 1237, Durango, Colorado

Oil and Gas Inspector Dist. #3.

(Title)

(Date)



OIL CONSERVATION COMMISSION		
AZTEC DISTRICT OFFICE		
No. Copies Received 3		
DISTRIBUTION		
	NO. FURNISHED	
Operator	1	
Santa Fe	1	
Proration Office		
State Land Office		
U. S. G. S.		
Transporter		
File	1	✓