## NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Poo	ol	meo	F	ormation	Nesa	Verde		County	Rio Ar	riba	
Initial X Annual			nual	Special				Date of Test9-3-57			
Com	pany Pacifi	le <b>Northre</b>	st Pipel:	ine	Lease	Sen Juan	31-6	We]	Ll No	11-31	- "- 1 1 11
Uni	t	Sec. 31	Twp31#	Rg	е <b>. б</b> ₩	Purc	haser <b>not</b>	connected	<u> </u>		
Cas	7-5/8 ing 5 1 1	/t	I.D.	Se	338 t at <u>564</u>	<b>27</b> <b>20</b> Pe:	rf	51.00	_To	5518	
Unit A Sec. 31 Twp. 311 Rge. 6W Purchasernot connected  7-5/8 Casing 5  Wt. I.D. Set at 5620 Perf. 5100 To 5518  Tubing 1-1/4 Wt. I.D. Set at 5566 Perf. To											
Gas Pay: From To L xG .550 GL Bar. Press. 12											
Producing Thru: Casing X Tubing Type Well Single Single-Bradenhead-G. G. or G.O. Dual											
Date of Completion:  Packer  Single-Bradenhead-G. G. or G.O. Dual Reservoir Temp.											
OBSERVED DATA											
Tested Through (Prover) (Choke) (Meter) Shut in 12 days Type Taps											
<b></b> _			Data			Tubing		Casing D		T	
No.		(Choke) (Orifice	Press.	Diff.	Temp.		Temp.	Press.			ration of Flow
	Size	Size	psig	h <sub>w</sub>	o <sub>F</sub> .	psig	°F.	psig	°F∙		Hr.
SI 1.		3/4"	263		670	1181 385		11.80 283	67		2 heurs
2 <b>.</b> 3 <b>.</b>									<u> </u>		
4.									<u> </u>		
5.											
FLOW CALCULATIONS											
No.	(24-Hour) √ h <sub>w</sub> i			essure	re Flow Temp. Factor Ft			Factor F <sub>pv</sub>		Q-MCFPD @ 15.025 psia	
				psia			$_{\mathtt{F}_{\mathtt{g}}}$				
1. 2.	14.1605			295	•9933		.9608	1.028		4098	
3. 4.											
5.											
PRESSURE CALCULATIONS  as Liquid Hydrocarbon Ratio cf/bbl. Specific Gravity Separator Gas ravity of Liquid Hydrocarbons deg. Specific Gravity Flowing Fluid c (1-e^-s) P_c											
No.	P <sub>w</sub>	Pt2	F <sub>c</sub> Q	$(F_cQ)^2$	(F	c <sup>Q)²</sup> -e <sup>-s</sup> )	<b>397</b> P <sub>w</sub>	$P_c^2 - P_w^2$		al.	P <sub>w</sub> P <sub>c</sub>
1. 2. 3. 4.							157.6	126.6	-		.12
3.											
4. 5.				<del></del>	<del></del>				<del></del>		
Absolute Potential: MCFPD; n .75/1.0887  COMPANY Pacific Borthest Pipeline Corporation  ADDRESS 1 Vest Brookey Farmington For Mexico  AGENT and TITLE C. R. Wagner - Well Test Engineer  WITNESSED											
COMPANY											
					I LEAD	atm.		OIL CON	Town	Parking and Species	

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure ( $P_{\rm W}$ ). MCF/da. @ 15.025 psia and 60° F.
- P<sub>c</sub> = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwT Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- $P_t$  Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- $P_{f}$  Meter pressure, psia.
- hw Differential meter pressure, inches water.
- FgI Gravity correction factor.
- $F_t$  Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If  $P_{\mathbf{W}}$  cannot be taken because of manner of completion or condition of well, then  $P_{\mathbf{W}}$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{\mathbf{t}}$ .

OIL CONSERVATION COMMISSION										
AZTEC DISTRICT OFFICE										
No. Copies Received										
DISTRIBUTION										
	NO. FURWISHED									
Úprarato:										
Santa Fa		-								
Profession Office										
State Land Office										
u. 3 G. 3.	/									
Transporter										
File		,								
400000000000000000000000000000000000000		i i								