

APPROVED

Form 9-331a
(Feb. 1951)


OCT 8

1- WSCS

1- W. Johnston

1- File

(SUBMIT IN TRIPLICATE)

Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.Land Office Santha FeLease No. 87 079165Unit None

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Report of Drilling & well Compl</u>	<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

August 21, 1956

Well No. 15-29 is located 1600 ft. from [N] line and 1120 ft. from [E] line of sec. 29

32 1/4 NE 1/4 29 31 N 5 W RMN
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Wildcat NY San Antonio New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the ingraded Ground above sea level is 6309.5 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total depth 5913', perf. 5706-5800', 5806-10', w/2 shots/ft., 5814-20', w/3 shots/ft., 5834-30', w/2 shots/ft., 5848-36', w/3 shots/ft., pressured up with 3000' had no HD. Re-perf. 5706-5800', w/3 shots/ft., and 5720-26', 5728-34', 5738-42', 5744-48', w/3 shots/ft. & 5748-48', w/2 shots/ft., pressured up to 3000' and had no HD. Spotted 300 gals 15% acid and broke down with 1400', max. 1700', to vac. From 521 w/44032 gals water and 60,000 / sd. HD 1200', avg. 1800', max. 2100', final 1900', to vac. II 61.3 BPM. Perf 5468-74', w/ 3 shots /ft., 5524-38', w/ 2 shots/ft. & 5560-44', w/3 shots/ft. 5568-72', 5584-38', w/ 3 shots/ft. 5692-5702', w/2 shots/ft. From Num. & CH w/ 52,500 gals. water only HD 800', avg. 1600', max. 1700', final 1600', stdg. 400' in 5 minutes. II 60.9 BPM. Cleared out to total depth ran tubing and completed well. Released rig 9:30 AM 8-22-56.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pacific Northwest Pipeline Corp.Address 403 1/2 W. BroadwayFarmington, New MexicoBy Original signed COMT. A. DuganTitle District Engineer