



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4.
Form Approved.

Land Office **Santa Fe**

Lease No. **078763**

Unit **Rosa Unit**

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL
NOTICE OF INTENTION TO CHANGE PLANS
NOTICE OF INTENTION TO TEST WATER SHUT-OFF
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL
NOTICE OF INTENTION TO SHOOT OR ACIDIZE
NOTICE OF INTENTION TO PULL OR ALTER CASING
NOTICE OF INTENTION TO ABANDON WELL

X

SUBSEQUENT REPORT OF WATER SHUT-OFF
SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
SUBSEQUENT REPORT OF ALTERING CASING
SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
SUBSEQUENT REPORT OF ABANDONMENT
SUPPLEMENTARY WELL HISTORY

RECEIVED

INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA.

August 28, 1962

Well No. **46** is located **890** ft. from **N** line and **1840** ft. from **E** line of sec. **8**
NE/4 Sec. 8 **31N** **5W** **N.M.P.M.**
(Q. Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco Mesa Verde **Rio Arriba** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6341** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Due to non-commercial production this well will be plugged & abandoned in the following manner:

1. Spot 35 sk. cement plug across perforations (5690 - 5464').
2. Determine free point on 7" casing, cut & pull.
3. Spot 35 sack cement plug across 7" casing stub.
4. Spot 20 sack cement plug at surface, install 4' x 4" dry hole marker.

RECEIVED
AUG 30 1962
OIL CON. COM.
DIST. 3

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **El Paso Natural Gas Company**

Address **Box 990**

Farmington, New Mexico

By **W. W. Meckan**

Title **Petroleum Engineer**