5. LEASE

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

GEOLOGICAL SURVEY	
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS OF COMMON CONTROL OF COMMON COM	
1. oil gas well other	Schalk 31-4 9. WELL NO.
2. NAME OF OPERATOR SCHALK DEVELOPMENT COMPANY	2 2 2 2 2 2 2
3. ADDRESS OF OPERATOR	Mesa Verde
P. O. BOX 25825	M. SEC., T., R., M., OR BLK. AND SURVEY OF
4. LOCATION OF WELL (REPORT LOCATION CLEARLY below.) 1845' FSL; 1670' FWL; Se	Sec. 33, T-31N, R-4W
AT SURFACE: T31N, R4W, Rio Arri	ba, NM 12. COUNTY OR PARISH 13. STATE New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATUR REPORT, OR OTHER DATA	E OF NOTICE, 15. ELEVATIONS (SHOW DF, KDB, AND WD
REQUEST FOR APPROVAL TO: SUBSEQUENT F	6657' GR
REQUEST FOR APPROVAL TO: SUBSEQUENT F TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE	ALPORT OF.
REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE	(NOTE: Report results of multiple completion or zon change on Form 9–330.)
CHANGE ZONES ABANDON* (other) DRILLING X	
(011101)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIO including estimated date of starting any proposed measured and true vertical depths for all markers are	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIO including estimated date of starting any proposed measured and true vertical depths for all markers are 779 Spud and drill 13-3/4" surf	work. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)*
17. DESCRIBE PROPOSED OR COMPLETED OPERATIO including estimated date of starting any proposed measured and true vertical depths for all markers are 779 Spud and drill 13-3/4" surf	work. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* [ace hole to 344'] [4' KBM. Cemented with 220 sxs class ack Flocelle. Plug down @ 10:15 pm]
17. DESCRIBE PROPOSED OR COMPLETED OPERATIO including estimated date of starting any proposed of measured and true vertical depths for all markers are 779 Spud and drill 13-3/4" surform 779 Set 8 jts 8-8/5" casing @34 'B' w/2% CaCl & 1/4# per sa	work. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* [ace hole to 344'] [4' KBM. Cemented with 220 sxs class ack Flocelle. Plug down @ 10:15 pm]
17. DESCRIBE PROPOSED OR COMPLETED OPERATIO including estimated date of starting any proposed of measured and true vertical depths for all markers are 779 Spud and drill 13-3/4" surform 779 Set 8 jts 8-8/5" casing @34 'B' w/2% CaCl & 1/4# per sare 779 Drilling 7-7/8" hole @ approximately approximately 19 Drilling 7-7/8" hole @ approximately 19 Drilling 7-7/8" hole	work. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* Face hole to 344! 4' KBM. Cemented with 220 sxs class ack Flocelle. Plug down @ 10:15 pm Poximately 2067! Set @ F
17. DESCRIBE PROPOSED OR COMPLETED OPERATIO including estimated date of starting any proposed of measured and true vertical depths for all markers are 79 Spud and drill 13-3/4" surform 79 Set 8 jts 8-8/5" casing @34 'B' w/2% CaCl & 1/4# per sare 79 Drilling 7-7/8" hole @ approximately approximately 19 Drilling 7-7/8" hole @	work. If well is directionally drilled, give subsurface locations and zones pertinent to this work.)* [ace hole to 344! [4' KBM. Cemented with 220 sxs class ack Flocelle. Plug down @ 10:15 pm [coximately 2067! [Set @ Fractionally drilled, give subsurface locations and the company of the content of the

JUL 13 1979