

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other Dry hole

2. NAME OF OPERATOR  
Resources Investment Corporation

3. ADDRESS OF OPERATOR  
3500 Anaconda Tower, Denver, CO 80202

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 860' FNL & 830' FWL (NW NW)  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒  
(other)

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE

NM 11929

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Rio Federal

9. WELL NO.

#1-35

10. FIELD OR WILDCAT NAME

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 35-T31N-R4W

12. COUNTY OR PARISH 13. STATE

Rio Arriba


New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

7083' KB

(NOTE: Report results of multiple completion or change on Form 9-331-C)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Operator proposes to P&A well as follows:

1. Squeeze Point Lookout perfs with 50 sx.
2. Set 25 sx. cement plug across top of liner at 4044'.
3. Perf 7" casing at +3500' and put 200' of cement on both the inside and outside of the 7" casing.
4. Perf 7" casing at +343' and put 100' cement plug across surface casing at 293'.
5. Set 10 sx. cement plug at surface.
6. Weld plate on casing head with dry hole marker.

Verbal approval received from Jim Sims on 2/6/81.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Don Hall TITLE District Engineer DATE 2/6/81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

APPROVED

FEB 23 1981  
JAMES F. SIMS  
OIL & GAS SUPERVISOR