

## NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

Off. Conservation division AZTEC DISTRICT OFFICE 1000 RIG BRAZOS ROAD AZTEC NM 87410 (606) 334-8178 FAX: (606) 334-8170 http://www.rd.edu.com/unicod/District NV3djetric.htm

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Page 1 Revised 11/16/98

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

perator <u>X/</u>	lions Roude	iton + Exp.	Lease Nar	ne <u>Ra</u>	su	Well No_ <i>80_0K/</i>	
ocation of V	Vell:Unit Letter	K_sec_	8 Twp.3/12	∕_Rge <u>.<i>5 ω</i></u>	_API#30-0 <u>3<i>9</i></u>	2253700	
	NAME OF RESERVOIR OR POOL			F PROD. vr Gas)	METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)	
Upper Completion	Misa Ven	de	las	<u> </u>	Flow	Thg.	
Lower Completion	NAKOTA		6-09		Flow	Thg.	
		PRE-	FLOW SHUT-	N PRESSUR	E DATA		
Upper	Hour, date shut-in Length of ti		Length of time	shut-in	SI press. Psig	Stabilized? (Yes or No)	
Completion Lower	Hour, date shut-in		Canada or anno	shut-in	195 195 SI press. Psig	Stabilized? (Yes or No)	
Completion	-7-31-01	12:10 PM		EST NO. 1	742	Ye5	
ommenced at (f	nour, date)*		1 2011 11	1	(Upper or Lower):		
TIME (hour,date)	LAPSED TIME	PRES	PRESSURE		E "	REMARKS	
	SINCE*	Upper Completion	Lower Completion	TEMP.			
12:10	22/ 4	19Z 195	742	98		27.20	
2-01 12:10	48	7 C 200	140	101	3 16 10	C1 C0 79 37 3	
					AL AV	40 3	
					RE	4 2001 W	
					O <sub>IL</sub> O		
						7.3	
oduction ra	te during test				•	3 WILES	
Dil:BOPD based on			d on	Bbls. inHours		GravGOR	
as:		MCF	PD; Tested thru	ı (Orifice or M	1eter):		
		MID	-TEST SHUT-I	N PRESSUR	E DATA		
Upper Completion	Hour, date shut-in		Length of time		SI press psig	Stabilized? (Yes or No)	
Lower Completion	Hour, date shut-in		Length of time	shut-in	shut-in SI press. psig Stabilized? (Yes or No)		

(Continue on reverse side)

FLOW TEST NO. 2

Commence	d at (hour, date)*	·•		Zone producing (Upper or Lowr):			
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion	URE Lower Completion	PROD. ZONE	REMARKS		
Oil: Gas:	ate during test BOPD			. inHour Orfice or Meter):	sGravGOR		
Mexico Oil Cor	nservation Division		Ву		bes of my knowledge.	_ New	

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial

packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests; immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result s of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).