

NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

Off. Conservation division AZTEC DISTRICT OFFICE 1000 RIO BRAZOS ROAD AZTEC NM 87410 (506) 334-8178 FAX: (506) 334-8170 http://www.rock/District.lik/Sdistric.htm

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

Page 1 Revised 11/16/98

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator	Williams Pl	Poil	Lease Nan	пө <u> Ягс</u> Г	A	Well No_ <i></i>		
ocation of \	Well:Unit Letter	A Sec S	7 <u>4</u> Twp_ <i>3//</i>	<u>√</u> Rge <u> </u>	✓_API#30-0 <u>3</u> 9	2348400		
	NAME OF RESE		F PROD. r Gas)	METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)			
Upper Completion	EL.		GAS		F/04	150		
Lower Completion	0.4.4		GAI		Floh	Thy		
		PRE	-FLOW SHUT-I	N PRESSUR	F DATA	/		
Upper Completion	Hour, date shut-in O Cy or S-10 - 0 / Hour, date shut-in		Length of time	shut-in	SI press. Psig 365 SI press. Psig	Stabilized? (Yes or No) () Stabilized? (Yes or No)		
Lower Completion	0901 F-1		96 6		305	149/		
Commenced at (hour, date)*			Zone producing	(Upper or Lower): Luce	2		
TIME (hour,date)	LAPSED TIME SINCE	PRES Upper Completion	SSURE Lower Completion	PROD. ZON TEMP.	NE REMARKS			
9608-14-0	1 24 has	365	375	65				
5008-14-	01 48 WS	375	140	72				
9008-14-	4068-14-01 72611 385		160	72	AUG A	3 200,		
						on of		
roduction ra	te during test				10 to	10 63		
Oil:		BOPD base	d on	Bbls. in	Hours	aravGOR		
Gas:	250	MCF	PD; Tested thru	ı (Orifice or N	Meter): <u>MeTen</u>			
		MID	-TEST SHUT-I	N PRESSUR	E DATA			
Upper Completion	Hour, date shut-in		Length of time	shut-in	SI press psig	Stabilized? (Yes or No)		
Lower	Hour, date shut-in		Length of time	shut-in	SI press. psig	Stabilized? (Yes or No)		

(Continue on reverse side)

FLOW TEST NO. 2

Commenced	l at (hour, date)*	*		Zone producing (Upper or Lowr):			
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion	URE Lower Completion	PROD. ZONE	REMARKS		
							
Production ra	te during test						
Oil: Gas:	BOPD	based onMCFF	Bbls PD:Tested thru (C	. inHour Orfice or Meter):	sGravGOF		
Remarks:						_	
Approved	fy that the inform AUG 2	9 2001 19_	Operator_	fell Hay	bes of my knowledge.	_ New	
OFBIGINAL S By	IGNIKO BY CHAPIL	JE T. PERVIN					
Title	V CAL & GAS INS	PECTOR, DIST. 🚜	Date <i>s</i>				

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial
- packer leakage test, a gas well is being flowed to the almosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadwoight pressure gauge at time intervals as follows: 3 hours tests: Immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result's of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).