

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease

State ☐

Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL ☐ GAS ☐ OTHER- Wildcat

2. Name of Operator  
Cambern and Associates Oil and Gas

3. Address of Operator  
Rt. 1, Box 501A, Amarillo, Texas 79106

4. Location of Well  
UNIT LETTER M 660 FEET FROM THE South LINE AND 660 FEET FROM  
THE West LINE, SECTION 28 TOWNSHIP 31N RANGE 3E NMPM.  
12 1S 2E

7. Unit Agreement Name

none

8. Farm or Lease Name

Hill Ranch

9. Well No.

1

10. Field and Pool, or Wildcat

Wildcat

Proposed Martin/Borders

15. Elevation (Show whether DF, RT, GR, etc.)

7866'KB

12. County

Rio Arriba

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER Completion ☒

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11/1/87 - TD 6 1/4" hole at 1165' at 11:00AM. Ran DILL, GR-FDC/CNL, and BHC Sonic logs. Ran 1151' of 4 1/2", 10.5#, J-55 casing. Set at 1155'. Cement with 160 sxs. of Class B w/ 2% CaCl.(188.8cf). Circ. cement to surface.

11/6/87 - MIRU completion rig. DO cement to 1165'. Drill ahead with 3 7/8" bit to 1182'. Perforate open hole from 1161'-1170' with 4 SPF. Acidize with 300 gals. MCA. Flow test well. Drill to 1223' with 3 7/8" bit. Ran GRN and E Log in new hole.

12/7/87 - Set inflatable packer from 1174' to 1180'. Swab test interval from 1155' to 1174'. No shows. Perforate open hole from 1166' to 1176' with 4 SPF. Acidize with 250 gals. MCA. Swab test well.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

TITLE Agent

DATE 4/7/88

M.D. Stricklin

Original Signed by FRANK T. CHAVEZ

SUPERVISOR DISTRICT #9

APR 07 1988

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: