

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

1. Name of Operator
Northwest Pipeline Corporation

2. Address of Operator
3539 East 30th - Farmington, NM 87401

3. Location of Well
UNIT LETTER G 1590 FEET FROM THE North LINE AND 1465 FEET FROM THE East LINE, SECTION 19 TOWNSHIP 31N RANGE 5W N.M.P.M.

4. Elevation (Show whether DP, RT, GN, etc.)
6340'

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.
SF-078764

7. Unit Agreement Name
Rosa Unit

8. Farm or Lease Name
Rosa Unit

9. Well No.
#204

10. Field and Pool, or Wildcat
Undes. Fruitland Coal

12. County
Rio Arriba

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPER. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER <u>Completion Operations</u> ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-8-88
MOL & RJ.

10-8-88
Drilled float collar and shoe. Hit coal zones as follows:
3101'-3107' - net coal 5'
3125'-3128' - net coal 5'
3133'-3144' - net coal 9'
3171'-3201' - net coal 28'
Total 47'. TD 3204'.

10-10
Blowing hole w/ air. Gauged well at 1630 hrs at 158 MCF/D.

10-11 thru 10-12
Blowing well with air.

10-13
Blowing well with air. Ran 5 jts (206') 5-1/2", 23#, P110 w/ Brown liner hanger. Texas

RECEIVED
OCT 31 1988
CIVIL DIV
LBB. S

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Carrie Harmon TITLE Prod. & Drlg. Clerk DATE 11-1-88

APPROVED BY Original Signed by FRANK T. CHAVEZ SUPERVISOR DISTRICT 8 DATE NOV 3 - 1988

CONDITIONS OF APPROVAL, IF ANY:

B

10-13 (continued)
pattern guide shoe on bottom. Set csg. from 2989' to 3204' KB (7" at 3055'). FC at 3203' KB.

10-14

Performed 5-1/2" P-110 liner as follows:

3201'-3203' 4 spt - 8 holes

3189'-3201' 4 spt - 48 holes

3169'-3189' 4 spt - 80 holes

3131'-3144' 4 spt - 60 holes

3121'-3130' 4 spt - 36 holes

3099'-3109' 4 spt - 40 holes

TIH w/ 2-7/8" tbgr. Landed deup w/ 100 jts 2-7/8", NU, 10 rd at 3172' KB. Expendable
check on bottom. "F" nipple between joints 1 & 2. NU wellhead. Pumped out plug. RD
fig.