

UNITED STATES
DEPARTMENT OF INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

RECEIVED
BLM
SUNDRY NOTICE AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION TO DRILL" for permit for such proposals

99 MAR -8 PM 1:33

070 FARMINGTON, NM

SUBMIT IN TRIPLICATE

| | |
|--|---|
| 1. Type of Well <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other | 5. Lease Designation and Serial No. SF-078772 |
| 2. Name of Operator WILLIAMS PRODUCTION COMPANY | 6. If Indian, Allottee or Tribe Name |
| 3. Address and Telephone No. PO BOX 3102 MS 37-2, TULSA, OK 74101 (918) 561-6254 | 7. If Unit or CA, Agreement Designation ROSA UNIT |
| 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 2045' FSL & 1960' FEL, NW/4 SE/4, SEC 3 T31N R6W | 8. Well Name and No. ROSA UNIT #238 |
| | 9. API Well No. 30-039-24501 |
| | 10. Field and Pool, or Exploratory Area BASIN FRUITLAND COAL |
| | 11. County or Parish, State RIO ARRIBA, NM |

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

| TYPE OF SUBMISSION | TYPE OF ACTION |
|--|---|
| <input checked="" type="checkbox"/> Notice of Intent | <input type="checkbox"/> Abandonment |
| <input type="checkbox"/> Subsequent Report | <input type="checkbox"/> Recompletion |
| <input type="checkbox"/> Final Abandonment | <input type="checkbox"/> Plugging Back |
| | <input type="checkbox"/> Casing Repair |
| | <input type="checkbox"/> Altering Casing |
| | <input checked="" type="checkbox"/> Other <u>Sidetrack and Cavitate</u> |
| | <input type="checkbox"/> Change of Plans |
| | <input type="checkbox"/> New Construction |
| | <input type="checkbox"/> Non-Routine Fracturing |
| | <input type="checkbox"/> Water Shut-Off |
| | <input type="checkbox"/> Conversion to Injection |
| | <input type="checkbox"/> Dispose Water |
| | (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) |

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Williams Production Company plans to sidetrack and cavitate this well as per the attached procedure. Estimated start date is April 1, 1999.

14. I hereby certify that the foregoing is true and correct

Signed SUSAN GRIGUHN

Title CLERK

Date February 11, 1999

(This space for Federal or State office use)

Approved by /S/ Duane W. Spencer

Team Lead, Petroleum Management
Title

Date

MAR - 4 1999

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

WILLIAMS PRODUCTION COMPANY
SIDETRACK & CAVITATION PROGNOSIS

Purpose: To sidetrack and cavitate this Fruitland Coal zone.

1. Prepare location, reserve pit, bank, and test anchors prior to rig move. Line pit.
Notify BLM 24 hours to moving in.
Spot all tanks. Spot air package.

Notify BLM 24 hours to moving in.
2. MIRUSU. Nipple up pneumatic actuated BOP's, 2 blooie lines, pneumatic working valves and 2 - 7" blooie lines. Anchor blooie lines securely. Test BOP's. Fill rig tank with produced water. Do not filter water unless necessary.
3. Rig up air package, 1800 cfm minimum.
4. TOOH w/ tubing and LD.
5. Set cmt retainer above liner top or above perfs. Sting into retainer.
6. Establish rate and squeeze perfs below retainer and 10' above retainer with class "B" cement..

SIDETRACK

Objective

KICK OFF ABOVE UPPER PERFS INSIDE CASING OR ABOVE LINER TOP INSIDE
INTERMEDIATE. DRILL TO TD.
LAND NEW LINER FROM KICKOFF POINT TO TD

7. On wireline set CIBP at kickoff depth just above a casing collar at a point with good cement bond preferably.
8. Pick up Whipstock(anchorstock) slide assembly and starter mill. TIH with DP, Drill Collars and one joint high grade drill pipe below drill collars. Refer to manufacturer's specs for all recommended milling weights, number of drill collars and RPM.
Tool length=16 1/2", Anchorstock whip=8' length, 3° whip face angle
9. Set bottom of slide assembly at by applying pressure down drill string. Approximately 3500 psi. May need pump truck.
10. Shear off from slide assembly. Approximately 45,000 psi over drag weight. Begin milling with starter mill.

Mill as per manufacturer's recommended procedure. Circulate with water.
 - a. Run starter mill with joint of high grade drill pipe, S-135, below drill collars. Drill approx. 16".
 - b. Run window mill with joint of drill pipe below drill collars. Mill length of whip face plus 10' into formation.
 - c. Run window mill and watermellon mill on drill collars. Make several passes through window to clean up burrs. Ream until smooth with no drag.