

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240DISTRICT II
P.O. Drawer DD, Artesia, NM 88210DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-039-24639
5. Indicate Type of Lease STATE ☐ FEE ☐
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name San Juan 31-6 Unit
8. Well No. 215
9. Pool name or Wildcat Basin Fruitland Coal
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6545GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE 'APPLICATION FOR PERMIT'
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL ☐ GAS WELL ☒ OTHER
2. Name of Operator Phillips Petroleum Company
3. Address of Operator 300 W. Arrington, Suite 200, Farmington, N.M. 87401
4. Well Location Unit Letter K : 2008 Feet From The S Line and 1780 Feet From The W Line Section 36 Township 31N Range 6W NMPM Rio Arriba County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 6545GL

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 6-24-90 - MIRU Aztec Well Service Rig No. 289. Spudded 12 1/4" hole at 12:00. Ran 9 5/8", 36# J-55, ST&C Casing set at 283'. RU DS and cemented with 250 sx Cl 'G' cement with 1/4# Gelflake/sk & 3% CaCl₂. Circ. 95 sx cement. Plugged down @10:30 and bumped plug with 400 psi. Float held. WOC 11 hrs. NUBOP.
- 6-28-90 - RU casing crew. Ran 7; 23#, J-55, LT&C casing set at 3152.53'. RU DS & cement w/500 sx 65/35 POZ w/12% gel & 1/4# gelflake/sk followed w/100 sx Cl G with 1/4# gelflake/sk, followed w/50 sx class G and 1/4# gelflake & 3/4 of 1% D-65. Circ 122 sx cem. Did not bump plug - Float held. Set slips with 60,000 #. RD & released rig.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE A.J. Kieke, Jr. TITLE Area Landman DATE 8-13-90
TYPE OR PRINT NAME A.J. Kieke, Jr. TELEPHONE NO. 505-599-3410

(This space for State Use)

Original Signed by FRANK T. CHAVEZ

APPROVED BY _____ TITLE SUPERVISOR DISTRICT DATE AUG 16 1990
CONDITIONS OF APPROVAL, IF ANY: