Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No.

SF-07899**9** 

## SUNDRY NOTICES AND REPORTS ON WELLS

6. If Indian, Allottee or Tribe Name

Do not use this form for proposals to di Use "APPLICATION FO	rill or to deepen or reentry to a different reservoir. R PERMIT—" for such proposals	
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
1. Type of Well		San Juan 31-6 Unit
Oil S Gas Other		8. Well Name and No. 219
2. Name of Operator		9. API Well No.
PHILLIPS PETROLEUM COMPANY		30-039-24672
3. Address and Telephone No. 300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400		10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		Basin Fruitland Coal
Unit K 1839' FSL & 1734' FWL Sec 34, T31N, RGW		11. County or Parish, State
	•	Rio Arriba, NM
12. CHECK APPROPRIATE BOX	(s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment Recompletion	Change of Plans New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
_ 00T 1	Casing Repair	☐ Water Shut-Off
Final Abandonment Notice	Altering Casing  X Other As Per NTL-FRA-90-1	Conversion to Injection
OIL CON DIVIONE AS PER NTL-FRA-90-1		Dispose Water (Note: Report results of multiple completion on Well
V 0422		Completion or Recompletion Report and Log form.)
13. Describe Proposed or Completed Operations (Clearly State a	If pertinent details, and give pertinent dates, including estimated date of startic cal depths for all markers and zones pertinent to this work.)*	ig any proposed work. If well is directionally drilled,
Description of cement job to fu the Ojo Alamo Formation, as per	1fill requirements for protection of	usable water zones including
Date: 6/12/90 Time St	arted: 0048 Time Co	mpleted:0153
Hole Size 8-3/4	asing Size 7" 23# J-55 New Casing	
Turbo Centralizers at 2592		
Spring Type Centralizers at 31		904 , 2815 .
Mud Flush 10 BB1s, Space	<del> </del>	
Mud Flush		
Lead Slurry500 sx C/G 65/3	5 POZ, 12% D20, 1/4#/sx D29, 11.7 ppg	@ 2,31 ft <sup>3</sup> /sx yield.
Mid Slurry		
Tail Slurry 150 sx C/G, 1/4	#/sx D29, 15.8 ppg @ 1.15 ft <sup>3</sup> /sx yiel	d

Displaced Plug with \_\_\_\_\_\_Bbls Fresh Water. Volume Cement Circulated 57 Bbls/Sacks Average Pressure 545 PSI, Average Rate 5 BPM, Bumped Plug with 1240 PSI. 14. I hereby certify that the foregoing is true and correct R. A. Allred Title Drilling Supervisor (This space for Federal or State office use) 

Title

SEP 26 1990