
Form 3160-5

UNITED STATES

FORM	(APPR	OVED
Budget Bun	cau No.	1004-0135
Expires:		

(June 1990) DEPART! BUREAU	Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No. SF-078999 6. If Indian, Allottee or Tribe Name 7. If Unit or CA, Agreement Designation			
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals				
SUBMIT IN TRIPLICATE				
1. Type of Well Oil X Gas Other		San Juan 31-6 Unit		
2. Name of Operator		221		
Phillips Petroleum Com	9. API Well No.			
3. Address and Telephone No. 300 W. Arrington, Suit	30-039-24934 10. Field and Pool, or Exploratory Area			
4. Location of Well (Footage, Sec., T., R., M., or Surve	Basin Fruitland Coa			
Unit K , 1368 FS/ 2/6	11. County or Parish, State			
Sec. 33, T31 N, R 6 W	Rio Arriba, NM			
12. CHECK APPROPRIATE BC	X(s) TO INDICATE NATURE OF NOTICE, REPOR	T, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION			
Notice of Intent	Abandonment	Change of Plans		
Subsequent Report	Recompletion Plugging Back	Non-Routine Fracturing		
Final Abandonment Notice	Casing Repair Altering Casing	Water Shut-Off Conversion to Injection		
	Other	Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)		
 Describe Proposed or Completed Operations (Clearly state give subsurface locations and measured and true we 	e all pertinent details, and give pertinent dates, including estimated date of starting a critical depths for all markers and zones pertinent to this work.)*	any proposed work. If well is directionally drilled,		
10-10-90				
MIRU Aztec Well Service Rig N	To. 301. Spudded 12-1/4" hole @ 6:00 PM.	Ran 9-5/8",		

36#, K-55, ST&C casing set @ 277.32'. RU Halliburton and cemented w/250 SX C1 "B" cement with 3% CaCl₂ and 1/4# Flocele/Sk. Circ. 90 SX cement. Plugged down A 4:00 AM 10-11-90. Bumped plug with 300 psi. Float held. WOC 10 hours. NU BOP and pressure tested BOP to 600 psi - okay.



	\					
14. I hereby certify that the top griffs is rule and corn Signed		Drilling	Supervisor	Comparison L	10-12-90	
(This space for Federal or State office use)			AC	KEPIEDI	OH HEGURD	==
Approved byConditions of approval, if any:	Tide			0CF 2	3 1990	
		FARMINGTON RESOURCE AREA				