Form 3160-5 (Jure 1990)

or representations as to any matter within its jurisdicti

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No.

SF-078995

FARMINGTON RESOURCE AREA

SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well San Juan 31-6 Unit Oil Gas Other 8. Well Name and No. 2. Name of Operator 225R 9. API Well No. PHILLIPS PETROLEUM COMPANY 3. Address and Telephone No. 30-039-24967 300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., K., M., or Survey Description) Basin Fruitland Coal 11. County or Parish, State Unit K, 2498' FSL & 1362' FWL Sec. 31, T31N, R6W Rio Arriba, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion **New Construction** Subsequent Report Plugging Back Non-Routine Fracturine Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Klother As Per NTL-FRA-90-1 Dispose Water Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1. Hole Size 8-3/4" Casing Size 7" 23# J-55 New Casing Seat 2818.07

Turbo Centralizers at 2254', 2167', 2122'.

Spring Type Centralizers at 2810' 10 Fresh Water. Mud Flush 10 BBls, Spacer Lead Slurry 500 SX 65/35 Poz, 12% Gel, 1/4# Flocele/Sk, 11.7 ppg @ 2.3 Ft³/Sk yield. Mid Slurry ----**Tail Slurry** 150 SX Class B, 1/4# Flocele/Sk, 15.6 ppg @ 1.18 Ft³/Sk yield. Displaced Plug with 107 __ Bbls Fresh Water. 156 Abds/Sacks Volume Cement Circulated Average Pressure 500 PSI, Average Rate 9 BPM, Bumped Plug with 1500 PSI. 14. I hereby certify that the foregoing is true and cor R. A. Allred Tide Drilling Supervisor (This space for Federal or State office use) Approved by ______ if any: Title ACCEPTED FOR RECORD **DCT 3.0 1990** Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements