Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED	
Budget Bureau No.	1004-0135
Expires: March	31, 1993

5. Lease Designation and Serial No.

SF-078999 SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals S 110 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 1. Type of Well San Juan 31-6 Unit Oil Gas Other 8. Well Name and No. 2. Name of Operator 9. API Well No. PHILLIPS PETROLEUM COMPANY 3. Address and Telephone No. 30-039-24972 300 West Arrington Suite 200, Farmington, NM 87401 505/599-3400 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., K., M., or Survey Description) Basin Fruitland Coal 11. County or Parish, State Unit H, 1999' FNL & 1280' FEL Sec. 34, T31N, R6W Rio Arriba, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12. TYPE OF SUBMISSION TYPE OF ACTION Abandonment Change of Plans Recompletion **New Construction** Plugging Back Subsequent Report Non-Routine Fracturing Casing Repair Water Shut-Off Altering Casing Conversion to Injection Final Abandonment Notice K Other As Per NTL-FRA-90-1 Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Description of cement job to fulfill requirements for protection of usable water zones including the Ojo Alamo Formation, as per NTL-FRA-90-1. __ Time Completed: 1400 Time Started: **Date:** 11-5-90 Casing Size 7" 23# J-55 New Casing Seat 3124 Hole Size 8-3/4" Turbo Centralizers at 2755' <u>, 2716'</u>, <u>2679'</u> Spring Type Centralizers at 3107', 3048',
Mud Flush 10 BBls. Spacer 10 Fresh Wa 29661 Mud Flush 10 BBls, Spacer Fresh Water. Lead Slurry 500 Sx 65/35 Poz, 12% Gel, 1/4# Flocele/Sk, 11.7 ppg @ 2.3 Ft³/Sx yield Mid Slurry _____ Tail Slurry 150 Sx Class B, 1/4# Flocele/Sk, 15.8 ppg @ 1.18 Ft³/Sk yield Displaced Plug with 119 Bbls Fresh Water. SMIN / Sacks Volume Cement Circulated PSI, Average Rate 5 BPM, Bumped Plug with 1200 PSI. 200 Average Pressure 14. I hereby opristy that the R. A. Allred ACCEPTED FOR BEFORD Tite Drilling Supervisor (This space for Federal or State office use)

Tide 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.