

In Southeast New Mexico

Completion

NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION AZTEC DISTRICT OFFICE 1000 RIO BRAZOS ROAD AZTEC NM 87410

(505) 334-8178 FAX: (505) 334-8170 http://www.nrd.state.nm.us/ood/District IM/3distric.htm This form is not to be used for reporting packer leakage tests

Page 1 Revised 11/16/98

	NO	RTHWEST NE	EW MEXICO	PACKER	R-LEAKAGE TEST		
Operator <u>(</u>	Villiams)	Dust	Lease Nam	ne	a Chit	Well No 100 E	
_ocation of \		_/Sec_Z	_Twp37	<u>X/</u> Rge <u>&</u> C	5API#30-0 <u>39</u> 2	513500	
	NAME OF RESER		F PROD. r Gas)	METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)		
Upper Completion	PC		60	5	How	The	
Lower Completion	my		bas	5	Alon	169	
	·	PRE-F	LOW SHUT-I	N PRESSUR			
Upper Completion	Hour, date shut-in		1-5	Si press. Palg	Stabilized? (Yes or No)		
Lower Completion	Hour, date shut-in	8-13-01		1115	SI press. Psig ZBO	Stabilized? (Yes or No)	
		= 3 -1/ /		ST NO. 1		-0	
Commenced at	1	3-16-8		PROD. ZON	(Upper or Lower): しゅう	REMARKS	
TIME (hour,date)	LAPSED TIME SINCE*	-	PRESSURE Upper Completion Lower Completion		201 III 201		
1115 80	774	83	280	70	65.26.21	28 29 30 37	
1115 848	4860	80	288	75	A111	1 3	
111 5 8-19	724,	80	292	77		2001 W	
					S Oil or Dis		
					(60)	- · · · · · · · · · · · · · · · · · · ·	
Production ra	ate during test				<u> </u>	a Line Disp	
Oil:		BOPD based	on	Bbis. in		ravGOR	
Gas: 16	4	MCFP	PD; Tested thru	ı (Orifice o r N	Meter): Meter		
		MID-	TEST SHUT-I	N PRESSUR	E DATA		
Upper Completion	Hour, date shut-in	Length of time	shut-in	SI press psig	Stabilized? (Yes or No)		
Lower	Hour, date shut-in	Length of time	shut-in	SI press. psig	Stabilized? (Yes or No)		

			FLOW TE	EST NO. 2			
Commenced at (hour, date)**				Zone producing (Upper or Lowr):			
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion	URE Lower Completion	PROD. ZONE	REMARKS		
·							

Production rate du	ring test					
Oil: Gas:	BOPD based onMCFP[Bbls. in D:Tested thru (Orfice or	Hours Meter):	Grav	GOR	_
Remarks:						_
Approved AL Mexico Oil Conservat	the information herein control of 2 9 2001 19 19 19 19 19 19 19 19 19 19 19 19 19	Operator	Lete to the beson	of my knowledg	e. WPX	_ New

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial

pecker leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.

- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadwoight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at lifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result's of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).