UNITED STATES				
DEPARTMENT OF INTERIOR		5. Lease Designation and Serial No. SF-078890		
BUREAU OF LAND MANAGEMENT				
SUNDRY NOTICES AND REPORTS ON WELLS		6. If Indian, Allottee	or Tribe Name.	
(Do not use this form for proposals to drill or to				
deepen or plug back to a different reservoir.		7. If Unit or CA, Agr	eement Designation.	
Use Form 3160-3 for such proposals.)			DOOR HINET	
1. Oil well [] Gas Well [X] Other []		ROSA UNIT		
Gas Well		8. Well Name and No	Rosa unit #288	
2. Name of Operator			RUSA UNIT - 200	
Evergreen Operating Corporation		9. API Well No. 🛴	30-039-25293	
3. Address & Telephone No. (505) 334-2555 c/o A. R. Kendrick, Box 516, Aztec, NM 87410				
4. Location of Well (Footage & S.T.R.)		Basin-Fruitland Coal Gas Pool		
1840' FSL 1020' FWL		11. County or Parish, State		
L - 4 - 31N - 4W		Rio Arriba, New Mexico		
12 CHECK APPROPRIATE BOX(s) TO INDICATE NATURE (F NOTICE, REPORT,	OR OTHER DATA	
[] Notice of Intent	[] Abandonment		[] Change Plans	
	[] Recompletion		[] New Construction	
[•] Subsequent Report	[] Plugging Back		[] Non-Routine Fracturing	
	[] Casing Repair		[•] Water Shut-Off	
[] Final Abandonment Notice	[] Alter Casing		[] Conversion to Injection	
	[•] Other	Spud	[] Dispose Water	
17. Describe Proposed of Completed	Operations (Give Pertinan	t Details and Dates.)	T AM LEVED	
Spud 20:00 hours 8/17/93.				
Drilled 12-1/4" hole to 395'. Ran 8-5/8" surface casing set at 395'.			38 NM	
Cemented w/268 CuFt (225.5	i y set at 390 . ix) Class B w/additives.	Circulated 67 CuFt	to surface. Weld on bradenhead.	
Cemented w/268 CuFt (225 Sx) Class B w/ additives. Circulated 67 CuFt to surface. Weld on bradenhead. Test casing ot 800 psi — held ok.				
Drilled 7-7/8" hole to TD =	4.000'.	4 4 4 4 - 4	(DO hamala mud flush 10	
8/22/93:Ran 5-1/2" casi	ng set ⊕ 3992". Cen JE Su\ E0 /E0 pozolop 2	nented St Stage S col	locele, tail in w/118 CuFt Class B	
neat w/0.4% Halad 344 and 1	:5 5X / 5U / 5U PUZUIUII , Z /2# /sv Flocele Stace t	ntals = 152 CuFt (1	25 Sx) Opened DV tool and	
circulated out 13 CuFt cement			j	
9/23/93 Comented 2nd st	ane w/20 harrels mud	flush, 1110 CuFt (6	500 Sx) Halilite w/2% CaCl2	
followed w/119 CuFt (100 St	x) Class B neat w/2% Ca	C12. Stage totals 12	29 CuFt (700 Sx). Circulated 103	
Cuft cement. Casing totals Closed DV tool w/1800 psi.	1581 Curt (825 5X)	<i>)</i> .	DECEIVED	
Released rig.				
Notice of Fig.			SEP - 3 1993	
			OU CON DIV	
NOTE: This format is issued in lieu of U.S. BLM Form 3160-5.			OIL CON. DIV.	
14. I hereby certify that the foregoing is true and correct.		A	DIST. 3	
Signed R Deuts	Title _	Agent	FOR FECOMBS	
Approved by	Title		ADT 3 1 1993	
Conditions of approval, if any:			FARMINGTON DISTRICT OFFICE	