

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT - " for such proposals

RECEIVED  
BLM

01 FEB 14 AM 10:05  
070 FARMINGTON, NM

6. Lease Designation and Serial No.

SF-078762

7. If Indian, Allottee or Tribe Name

8. If Unit or CA, Agreement Designation

9. Well Name and No.

Rosa Unit #131

10. API Well No.

30-039-25313

11. Field and Pool, or Exploratory Area

Basin Dakota

12. County or Parish, State

Rio Arriba New Mexico

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Amoco Production Company

Attention:

Julie L. Acevedo

3. Address and Telephone No.

P.O. Box 800 Denver, Colorado 80201

(303) 830-5427

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

940FSL

1660FEL

Section 12 Township 31N Range 5W

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Spud and Set

☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud a 17.5" surface hole on 11/25/93 at 03:30 hrs. Drilled to 400'.

Set 13.375' 61# J-55 surface casing at 395'. Cemented with

500 SX CL B Circulated 68 BBLS to the surface.

Pressure tested casing to 1500 psi. Drilled a 12.250" hole to a depth of

4050' on 12/08/93. Set 9-5/8 36# J-55 intermediate

casing at 4050'. Cemented with 1st Stg=575 SX CL B, 2nd Stg=800 SX CL B, Tail w/100 SX CL B, DV @ 2732'

Circulated 80 BBLS to the surface. Pressure tested casing to 1500 psi.

Drilled a 8.75" hole to a depth of 7879' on 12/20/93. Set 7" 23# J-55 protective casing at 7879'. Cemented with 555 SX 50/50 POZ, 275 SX 50/50 POZ DV @ 5137 TOC @ 1700'.

Drilled a 6.250" hole to a TD depth of 8550' on 1/3/94. Plug well back with 240 SX CL G. plug from 8550' to 7680' tested casing to 500 psi. 0%.

Rig released at 1400 hrs. on 01/03/94.

14. I hereby certify that the foregoing is true and correct

Signed

Title

Sr. Staff Assistant

Date

01-20-1994

(This space for Federal or State office use)

Approved by

Title

ACCEPTED FOR RECORD  
Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.