

NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION
AZTEC DISTRICT OFFICE
1000 RIO BRAZOS ROAD
AZTEC NM 87410
(506) 334-6170
n Samand etata nm unfocul/District Mathematic bet

Page 1 Revised 11/16/98

This form is not to be used for reporting packer leakage tests in Southeast New Mexico http://www.nrd.state.nm.us/odd/District IN/3distric.htm

	NO	RTHWEST NE	W MEXICO	PACKER	R-LEAKAGE TEST			
Operator	Is lliams	· Durd	_Lease Nan	10 K 0	sa Unit	Well No 5 A		
Location of \	Well:Unit Letter_	P. sec 2 4		<u> </u>	∪API#30-0 <u>392</u>	540700		
	NAME OF RESERVOIR OR POOL			F PROD. r Gas)	METHOD OF PROD. (Flow or Art. Lift)	PROD.MEDIUM (Tbg. or Csg.)		
Upper Completion	PC		699		Dow	The		
Lower Completion	my		695		flow	The		
		PRE-FI	LOW SHUT-I	N PRESSUR	E DATA	,		
Upper	Hour, date shut-in		Length of time		SI press, Psig	Stabilized? (Yes or No)		
Completion	1000	8 ~13~0	172	h-5	515	YC5		
Lo we r Comp let ion	Hour, date shut-in	8-13-01	Length of time	1 11 5	SI press. Psig 253	Stabilized? (Yes or No)		
			FLOW TE	ST NO. 1				
Commenced at (hour, date)* $8 - 16 - 01$ /D			000	Zone producing (Upper or Lower): UPPER				
TIME (hour,date)	LAPSED TIME SINCE*	PRESSU Upper Completion 1	ower Completion	PROD. ZON TEMP.	E RE	EMARKS		
1000 8-17	74 hrs	220	260	75	7267	179.22		
1000 8-18	48 645	215	260	75	12 COC	4 CO (3)		
1000 8-19	726,5	198	260	>8	AU DAU	G 2001		
						\$7/4600 P		
					46			
Production ra	ate during test							
Oil:	Oil:BOPD based onBbls. inHoursGravGOR							
Gas:	540	MCFPI	D; Tested thru	(Orifice or N	Meter): Mexer			
		MID-T	EST SHUT-I	N PRESSUR	E DATA			
Upper Completion	Hour, date shut-in		Length of time		SI press psig	Stabilized? (Yes or No)		
Lower Completion	Hour, date shut-in		Length of time	shut-in	SI press. psig	Stabilized? (Yes or No)		

(Continue on reverse side)

FLOW TEST NO. 2

Commenced at (hour, date)**				Zone producing (Upper or Lowr):		
TIME	LAPSED TIME	PRESS	URE	PROD. ZONE	REMARKS	
(hour,date)	Since**	Upper Completion	Lower Completion	11100120112	NEMARA8	
	ite during test	Ll				
					sGravGOR	
Remarks:						
Remarks: hereby certi		pation herein con	itained is true and	complete to the	bes of my knowledge.	
hereby certi hereby certi hpproved_ dexico Oil Cor	fy that the inform	ation herein con	tained is true and	I complete to the	bes of my knowledge.	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the wellhead pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial
- packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result's of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).