

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT--" for such proposals

5. Lease Designation and Serial No.  
SF-078771

6. If Indian, Allottee or Tribe Name

**SUBMIT IN TRIPLICATE**

1. Type of Well  
☐ Oil Well ☒ Gas Well ☐ Other
2. Name of Operator  
NORTHWEST PIPELINE CORP.
3. Address and Telephone No.  
P. O. BOX 58900 MS 2M3 SALT LAKE CITY, UTAH 84158-0900 (801) 584-6981
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
983' FNL & 1029' FEL, SEC. 26, T31N, R6W

7. If Unit or CA, Agreement Designation  
ROSA UNIT

8. Well Name and No.  
ROSA UNIT #144

9. API Well No.  
30-039-25421

10. Field and Pool, or Exploratory Area  
WILDCAT; ROSA PICTURED CLIFFS

11. County or Parish, State  
RIO ARriba COUNTY, NM

**CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

**TYPE OF SUBMISSION**

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other COMPLETION OPERATIONS

**TYPE OF ACTION**

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water  
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9-17-94  
Clean out to PBTD at 3310'.

9-18-94  
RU isolation tool and pressure test to 4000# - OK. Petro perforated 3121' to 3127' (4 holes), 3140' to 3156' (9 holes), 3163' to 3167' (3 holes), 3178' to 3192' (8 holes), and 3196' to 3220' (13 holes). Total of 37 (0.36") holes shot at 1 hole/2'. Western fraced with 101,560# of 20/40 sand in 70 quality nitrogen foam at 1 - 5 ppg. Job completed at 1430 hrs 9/17/94. ISIP = 1200#. ATP = 2350#; AIR = 30 BPM; MTP = 2430#; MIR = 31.5 BPM. Used 472,865 SCF of nitrogen and 448 bbls of cross-linked borate gel.

9-21-94  
Ran 100 jts. (3196.62') of 1-1/2", 2.9#, J-55, EUE 10rd tubing with notched collar on bottom and SN (1.375" ID @ 3175') on top of bottom joint. Landed @ 3208' KB. Rig released at 0800 hrs 9/21/94.

14. I hereby certify that the foregoing is true and correct

Signed KATHY BARNEY Title SR. OFFICE ASSISTANT Date 09/21/94

(This space for Federal or State office use)

Approved by \_\_\_\_\_ Title \_\_\_\_\_ Date \_\_\_\_\_

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

SEP 28 1994

ACCEPTED FOR RECORD  
FARMINGTON DISTRICT OFFICE  
BY Sum