NEW MEXICO ENERGY, MINERALS & NATURAL RESOURCES DEPARTMENT

OIL CONSERVATION DIVISION
AZTEC DISTRICT OFFICE
1000 RIO BRAZOS ROAD
AZTEC NM 87410
(506) 334-6176 FAX; (506) 334-6170
http://www.rd.cod/District M/3distric.htm

orm is not to
sed for reporting
cher leakage tests
Southeast New Mexico

Page 1 Revised 11/16/98

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator	MAC	·	Lease Na	me <u>/く</u> りご	A MULT	Well No_148 (
Location of	Well:Unit Letter		<u> </u>	<u>/</u> \/ Rge <u>(</u>	<u>ധ</u> API#30-0 <u>3</u>	92549306		
	NAME OF RESE	1	PROD. or Gas)	METHOD OF PRO				
Upper Completion	MESA VERNE		Ga	5	Flow	<u>¢\$6</u>		
Lower Completion	Dakoro	Ga	<u> </u>	FLow	TEG			
		PRE-I	FLOW SHUT-	N PRESSUR	RE DATA			
Upper	er Hour, date shut-in		Length of time		SI press. Psig	Stabilized? (Yes or No)		
Completion	1155 8.3.01				240	185		
Lower	Hour, date shut-in		Length of time		SI press. Psig	√€ Stabilized? (Yes or No)		
Completion	ton 1155 8.3.01				252	yes		
				ST NO. 1		/		
Commenced at (hour, date)* 11 55 8-6-			-01	Zone producing (Upper or Lower): Low Eve				
TIME (hour,date)	LAPSED TIME SINCE*	PRESS	URE	PROD. ZON	E REMARKS			
		Upper Completion	Lower Completion	TEMP.				
55 8-7	24 HRS	240	216	29,	5	07.20.20.20		
55 8-8	48 HRS	243	184	86		100 CO 10		
55 8-9	724185	248	172	866		Allo con de		
				<u></u>		AUG 2001		
			- , <u>- </u>			RECEIVED 너		
						1 00 00 s		
·		LL_			\ <u>\</u>			
	te during test				4	8.51.11.31.11.11.11.11.11.11.11.11.11.11.11		
il:BOPD based on			on	Bbls. inHoursG		_GravGOR		
as:	119	MCFP	D; Tested thru	(Orifice or M	eter): ^ ET	ēr.		
		MID-T	EST SHUT-IN	PRESSURE	E DATA			
Upper Completion	Hour, date shut-in		Length of time s		SI press psig	Stabilized? (Yes or No)		
Lower Completion .	Hour, date shut-in	Length of time s	hut-in	SI press. psig	Stabilized? (Yes or No)			

(Continue on reverse side)

FLOW TEST NO. 2

Commenced	i at (hour, date)*	*		Zone producing (Upper or Lowr):			
TIME (hour,date)	LAPSED TIME Since**	PRESS Upper Completion	URE Lower Completion	PROD. ZONE	REMARKS		
							
Production ra	ite during test						
Oil: Gas:	BOPD	based onMCFI	Bbls PD:Tested thru (0	s. inHour Orfice or Meter):	rsGravGOR		
Remarks:							
Approved	fy that the information AUG 2	9 2001 19	Operator	wpx	bes of my knowledge.	New	
	IAL STONES BY OH	IAPILIE T. PERFEN	_	USS CI III	evez Ech		
	Y ON & GAS INST			_		- 	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of
- a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test no. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at lifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the beginning of each flow period, at least one time during each flow period. (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The result s of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico oil Conservation Division on northwest new Mexico packer leakage Test Form Revised 11-16-98 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).