In Lieu of Form 3160-5 (June 1590)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED
Budget Bureau No. 1004-0135
C M 21 1002

Expires: March 31, 1993

	ALUE IV
SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to deepen or reentry to a different r	RI M
Do not use this form for proposals to drill or to deepen or reentry to a different r	eservoir. Use

Lease Designation and Serial No. SF-078763

If Indian, Allottee or Tribe Name "APPLICATION FOR PERMIT--" for such proposals If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE **ROSA UNIT** Well Name and No. Type of Well **ROSA UNIT #41A** Oil Well IXI Gas Well □ Other Name of Operator API Well No. NORTHWEST PIPELINE CORPORATION 30-039-25506 Field and Pool, or Exploratory Area Address and Telephone No. 10 PO BOX 58900 MS 2M3, SALT LAKE CITY, UTAH 84158-0900 (801) 584-6879 **BLANCO MESAVERDE** Location of Well (Footage, Sec., T., R., M., or Survey Description) County or Parish, State 2180' FSL & 1485' FEL, SEC 5, T31N, R05W RIO ARRIBA, NEW MEXICO

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION ☐ Change of Plans □ Notice of Inten □ Abandonment ☐ New Construction ☐ Recompletion XI Subsequent Re ☐ Plugging Back □ Non-Routine Fracturing ☐ Water Shut-Off ☐ Casing Repair ☐ Conversion to Injection ☐ Final Abandonmen ☐ Altering Casing M Other DRILLING OPERATIONS ☐ Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. 13. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5-09-95 Move on location and rig up. Spud surface hole at 1445 hrs 5/8/95. TD surface hole at 287'. Ran 6 jts. (275.19') of 9-5/8", 36# and 40#, K-55, LT&C and ST&C casing and landed at 287' KB. Cemented with 150 sx (177 cu.ft.) of Cl "B" with 3% CaCl2 and 1/4# celloflake/sk. Displaced plug with 19 bbls of water. Plug down at 0100 5/9/95. Circulated out 8 bbls cement to surface.

5-10-95 Pressure test casing & BOP to 1500#.

5-12-95 TD intermediate hole at 3550' with bit #3 (8.75, HTC, O5C).

5-13-95 Ran 83 jts (3538.71') of 7", 20#, K-55, ST&C casing and landed at 3550'KB. Float collar at 3520'. BJ cemented with 410 sx (841 cu.ft.) of Cl "B" with 2% CaCl2, 8% gel, and 1/4# cello-flake/sk. Tailed with 175 sx (207\_cu.ft.) of Cl "B" with 2% CaCl2 and 1/4# cello-flake/sk. Displaced cement with 143 bbls of water and plug down at 1245 hrs 5/12/95. Circulated 7 Bbls of scavenger cement to surface. Pressure test BOP and casing to 1500# - held OK. Well dusting at 0415 hrs 5/13/95.

5-16-95 Schlumberger ran IND/GR, CDL/SNL and TEMP logs. Ran 58 jts (2532.92') of 4-1/2", 10.5#, K-55, ST&C casing and landed at 5945 KB. Float collar at 5922'. Marker joint at 5230'. Top of liner hanger at 3412). BJ cemented with 245 sx (424 cu.ft.) of Cl "B" with 4% gel, 6-1/4# gilsonite/sk, and CF14 (fluid loss). Displaced cement with 65 bbls of water and plug down at 1430 hrs 5/15/95. Reversed out 5 bbls of cement.

14.	I hereby certify that the foregoing is true an Signed SUSAN GRIGUIIN		Title CLERK	Date May 18, 1995
	<del></del>	Maria Company	THE CLERK	Date (Ma) 10, 1773
	(This space for Federal or State office use)	ant. 4	Date	
	Approved by Conditions of approval, if any:	Title	Date	
			40050	ED FOR RECORD

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side

FARMINGTON DISTRICT OFFICE