

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil ☒ Gas ☐ Other
☐ Well ☒ Well ☐ Other

2. Name of Operator

VASTAR RESOURCES, INC.

3. Address and Telephone No.

1816 E. MOJAVE ST., FARMINGTON, NM 87401 (505) 599-4300

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2405' FSL, 1880' FWL, Section 18, T32N, R4W

K2, T2, N, R SW

5. Lease Designation and Serial No.

NM 68762

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

CARRACAS 2 A #11

9. API Well No.

30-039-28474

10. Field and Pool, or Exploratory Area

BASIN FRUITLAND COAL

11. County or Parish, State

RIO ARRIBA COUNTY, NM

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	
☐ Notice of Intent	☐ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment Notice	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☒ Other <u>DRILLING OPERATIONS</u>
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut-Off
	☐ Conversion to Injection
	☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

8-29-00 Spud 12 1/4" hole @ 13:00. TD'd surface hole at 430' on 8-29-00 @ 19:00. Ran 9 joints 8 5/8" 24# J-55 STC casing to 424' and cemented with 333 sx Class B w/ 3% CaCl2 & 1/4 #/sx Floceal. Circulated 34 bbls cement to pit. Installed bradenhead & BOP. Tested BOP to 250 psi low 2000 psi high. Tested casing to 500 psi. Drilled out with 7 7/8" bit.

9-3-00 TD'd 7 7/8" hole at 3228' @ 19:30. Ran 79 joints 5 1/2" 17# K-55 LTC casing to 3228' and cemented with 695 sx 65/35 B/Poz w/ 6% gel, 5 #/sk Gilsonite & 1/4PPS Floceal followed by 100 sx 50/50 B/Poz w/ 2% gel 0.4% haled 344, 5 #/sk Gilsonite & 1/4PPS floceal. Circulated 94 bbls cement to pit. CIP 16:00 9-4-00. ND BOP, NU Wellhead, RD.

cc: BLM, Farmington (Or + 3)

N. Hall

Well File

14. I hereby certify that the foregoing is true and correct

Signed Charles W. Kuehn

Title Engineer 505 599 4308

Date 9-5-00

(This space for Federal or State office use)

Approved by _____

Title _____

Date _____

Conditions of approval, if any:

ACCEPTED FOR RECORD
9-5-00

DEC 08 2000

ADMINISTRATIVE OFFICE
BY [Signature]

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side