

A 10x10 grid with the number 32 in the center. The number 32 is written in a bold, black, sans-serif font, positioned in the fourth column from the left and the fourth row from the bottom. The grid lines are thin and black, forming a uniform pattern of squares.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

**Santa Fe, New Mexico**

## WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

**PACIFIC NORTHWEST PIPELINE CORPORATION**  
(Company or Operator)

**ROMA**  
(1 am)

Well No. 26-32, in NE ¼ of NE ¼, of Sec. 32, T. 31 North, R. 5 West, NMPM.

Blanco Mesa Verde Pool, Rio Arriba County.

Well is 725' feet from North line and 700' feet from East line

of Section 32..... If State Land the Oil and Gas Lease No. is E-347-28

Drilling Commenced August 4th, 1957 Drilling was Completed September 11th, 1957

Name of Drilling Contractor..... **Sage Drilling Company**

Address.....Farmington, New Mexico.....

Elevation above sea level at Top of Derriek Floor 6539' The information given is to be kept confidential until  
19.....

### OIL SANDS OR ZONES

No. 1, from 5544 to 5958 No. 4, from \_\_\_\_\_ to \_\_\_\_\_

No. 2, from.....to..... No. 3, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to feet

No. 2, from ..... to ..... feet.

No. 3, from.....to.....feet.

No. 4, from ..... to ..... feet.

### CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
10-3/4"	32.75	New	229'	Tex. Pat.			
7-5/8"	26.4	New	3816.86'	Guide & Float Collar			
5-1/2"	15.50	New	2301.08'	Guide & Float Collar			
1-1/4"	2.3	New	5860.34'	Tubing w/perf nipple			

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
13-3/4"	10-3/4"	240'	200	Pump Plug		
9-7/8"	7-5/8"	3830'	200	Pump Plug		
6-3/4"	5-1/2"	6024.06'	200	Pump Plug		
4-3/4"	2-1/4"	5870.34'	TUBING			

RECEIVED  
 FEB 13 1958

### RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Perf w/2 shots per foot, 5958-54, 5942-38, 5980-14, 5910-5900, 5896-54, 5844-40, 5836-30, 5828-24, 5694-88, 5660-54, 5646-40, 5590-80, 5548-44. Free w/126,000 gals water. NP 1000# to 800#, IP 800#, Avg. 1180#, MP after 190 balls 2550#. IR before balls 47 bbls/min. Avg IR 38 bbls/min. FP 1600#, standing 900#.

**Result of Production Stimulation.....**

**...Depth Cleaned Out... 6025'**