

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Santa	8	, -
Unit San	Juan OD-001	30-4	<u>Unit</u>

SUNDRY NOTICES AND REPORTS ON WELLS

		الحجها		, ,
NOTICE OF INTENTION TO DRILL		X	SUBSEQUENT REPORT OF WATER SHUT-OFF	1
NOTICE OF INTENTION TO CHANGE PLAI		J 18	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER		1 11	SUBSEQUENT REPORT OF ALTERING CASING	i i
NOTICE OF INTENTION TO RE-DRILL OR	REPAIR WELL	-	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	1 1
IOTICE OF INTENTION TO SHOOT OR A	CIDIZE	-	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALT	TER CASING	-	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WE	11	-		
(INDICATE	ABOVE BY CHECK MAR	RK NATU	IRE OF REPORT, NOTICE, OR OTHER DATA)	
			<u>Cetober 1</u>	, 1953
(K Sec. and Sec. No.)	31 K (Twp.)	(Rang	line and 1650 ft. from W line of M. P. M. (Meridian)	
ildeat	Ric A	rrib	division) (State or Territory)	Jan 19
(Field)	(County	y or sub	division) (State or Territory)	
	bjective sands; show s ing points, and all	izes, we l other i	OF WORK sights, and lengths of proposed casings; indicate muddimportant proposed work) ng rotary tools through the Se	
It is intended to drawtion, and to drill	bjective sands; show s ing points, and all irill a well, the Mesaverd	izes, we l other i	sights, and lengths of proposed casings; indicate muddi important proposed work)	saverde ot the
It is intended to demention, and to drill tire pay section with Casing Program: 9-5/8" at 172"	bjective sands; show sing points, and all little a well, the Messaverd 2 quarts of	izes, we lother in the winds.	ights, and lengths of proposed casings; indicate muddimportant proposed work) ng rotary tools through the Me. th gas circulation, and to show. G. per foot. Total depth 6040	ot the
It is intended to demention, and to drill tire pay section with Cosing Program: 9-5/8" at 172"	bjective sands; show sing points, and all little a well, the Messaverd 2 quarts of	izes, we lother in the winds.	ights, and lengths of proposed casings; indicate muddimportant proposed work) ng rotary tools through the Me. th gas circulation, and to show. G. per foot. Total depth 6040	ot the
It is intended to drawtion, and to drill tire pay section with Casing Program: 9-5/8" at 172" 7" at 5600"	bjective sands; show a ing points, and all irill a well, the Messaward 2 quarts of with 125 asc with 500 sac	izes, we lother in the wind selection of the	ights, and lengths of proposed casings; indicate muddimportant proposed work) Ing rotary tools through the Marith gas circulation, and to show the per foot. Total depth 6040 of regular coment circulated to depth against coment.	ot the
It is intended to drawtion, and to drill tire pay section with Casing Program: 9-5/8" at 172" To at 5600"	bjective sands; show a ing points, and all irill a well, the Messaward 2 quarts of with 125 asc with 500 sac	izes, we lother in the wind selection of the	ights, and lengths of proposed casings; indicate muddimportant proposed work) ng rotary tools through the Me. th gas circulation, and to show. G. per foot. Total depth 6040	ot the
It is intended to drawtion, and to drill tire pay section with Casing Program: 9-5/8" at 172" To at 5600"	bjective sands; show a ing points, and all irill a well, the Messaward 2 quarts of with 125 asc with 500 sac	izes, we lother in the wind selection of the	ights, and lengths of proposed casings; indicate muddimportant proposed work) Ing rotary tools through the Marith gas circulation, and to show the per foot. Total depth 6040 of regular coment circulated to depth against coment.	eaverde ot the
It is intended to drawtion, and to drill tire pay section with Casing Program: 9-5/8" at 172" To at 5600"	bjective sands; show a ing points, and all irill a well, the Messaward 2 quarts of with 125 asc with 500 sac	izes, we lother in the wind selection of the	ights, and lengths of proposed casings; indicate muddimportant proposed work) Ing rotary tools through the Marith gas circulation, and to show the per foot. Total depth 6040 of regular coment circulated to depth against coment.	ot the
It is intended to desertion, and to drill three pay section with Casing Program: -5/8" at 172" The Wg of Section	bjective sands; show a ing points, and all irill a well, the Messwerd 2 quarts of with 125 and with 500 and tion 33 is de	izes, we i other i oth	ights, and lengths of proposed casings; indicate muddimportant proposed work) ng rotary tools through the section, and to should get foot. Total depth 6040 of regular coment circulated to fregular coment.	surface.
It is intended to dramation, and to drill tire pay section with Casias Program: -5/8" at 172" The woof Section with the se	bjective sands; show sing points, and all irill a well, the Messwerd 2 quarts of with 125 sec with 500 sec irin 33 is de	izes, we i other i other i other i se wi se	ights, and lengths of proposed casings; indicate muddimportant proposed work) Ing rotary tools through the Marith gas circulation, and to show the per foot. Total depth 6040 of regular coment circulated to depth against coment.	surface.
It is intended to description, and to drill tire pay section with Casing Program: 9-5/8" at 172" The Wg of Section	bjective sands; show a ing points, and all little a well, the Nessward 2 quarts of with 125 and with 500 and	izes, we lother in writing the will consider the writing the writing the will consider the will consid	ights, and lengths of proposed casings; indicate muddimportant proposed work) ng rotary tools through the section, and to should get foot. Total depth 6040 of regular coment circulated to fregular coment.	surface.
It is intended to drawtion, and to drill tire pay section with Casiar Program: -5/8" at 172" The way of Section work in the pay of Section work in the pay of Section work in the page of Section with the page of	bjective sands; show a ing points, and all irill a well, the Messaverd 2 quarts of with 125 and with 500 and the irin 33 is defined as the control of the co	izes, we i other i oth	ights, and lengths of proposed casings; indicate muddimportant proposed work) ng rotary tools through the section, and to should get foot. Total depth 6040 of regular coment circulated to fregular coment.	surface.