# STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

## OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

# NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Acerian			G LTD PARTNERS	SHIP Lease	State	Com R	Well 14(PM	I)
of Well:	Unit	M Sec3	6 Twp30	Rge	9	Cou	unty San Juan	
410		NAME OF RESE	INVOIR OR POOL	IR POOL TYPE OF F		METHOD OF PRO	D. PROD. MEDI	
Upper	PICTURE		IRED CLIFF	GAS		· FLOW	TBG.	
empletion MESA VERD			VERDE	E GAS		FI.OW	TBG.	<del></del>
			PRE-FL	OW SHUT-IN F	RESSURE DA			
Upper empletion	Hour, date s	04-14-91	Length of time on	iut-in	SI press. pelg	<del></del>	Stabilized? (Yes or No)	
	Hour, date s		3-DAY	KS	81 press, paig	30	L NO	
empletion			1 .	3-DAYS		25	Stabilized? (Yes or Ho)	
							NO	
Attronood	ol (hour, dal	4*	04-17-91	FLOW TEST		(Upper or Lowerk		
TIM (hour, c	-	LAPSED TIME SHICE#	PRES Upper Completion	Lower Completion	PROD. ZONE		Lower	<del></del>
04-1	.5-91	1-DAY	212	215	18.00		, manufacture	
		·	212	215	<del> </del>	ROTH Z	ONES SHUT-IN	<del></del> -
04_1	6-91	2-DAYS	225	225		BOTH Z	ONES SHUT-IN	
04-1	7-91	3-DAYS	230	237			ONES SHUT-IN	
04-1	8-91	1÷DAY	230	451			ZONE FLOWING	-
_04-1	9-91	2-DAYS	232	451				******
						- IJWF.K	ZONE FLOWING	
oductio	n rate di	uring test						
il:		ВС	PD based on	Bbls. in	Но	urs	Grav GOR	
25:		613	МСЕ	PD; Tested thru			ETER_	
				EST SHUT-IN PI				
Upper :	lovr, dale er	rut-in	Langth of time she	#in	St busser beid	Λ	Stabilized? (Yes or No)	
Lower	Hour, date shut-in		Longth of time shy	Longth of time shut-in			Stabilized? (Yes or No)	
			·				FIAFU	
		•	٠			MAY	′3 <b>0</b> 199 <b>1</b> ,	

(Continue on reverse side)

OIL CON. DIV.

#### FLOW TEST NO. 2

TIME	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE		
(frour, date)		Upper Completion	Lower Completion •	TEMP.	REMARKS	
	İ		1			
		·				
					•	
· · · · · · · · · · · · · · · · · · ·		<del> </del>			The second secon	
·	<del> </del>					
Gas:61	BOP	мс	FPD: Tested thru	(Orifice or Meter	Grav GOR	
I hereby certify the	hat the informat MAY 3 () 1	1991	ned is true and co	emplete to the bes	of my knowledge.  OPERATING LTD PARTNERSHI	
New Mexico C	il Conservation	Division			/// / / · · · · · · · · · · · · · · · ·	
New Mexico C	Oil Conservation of Signed by CHAR	Division .	1	by K. H. M.	flile/th.	

## NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and anoually thereafter as prescribed by the order authorizing the multiple completion. Such sests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tosts shall also be taken at any time that communication is suspected or when requested by the Division.

d at flower databilities

- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure subilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains short-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well, Notes if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, is accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is so be the same as for Flow Test No. 1 energy

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-sone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-missure intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day sesse: immediately prior to the beginning of each flow period, at least one time during each flow period (at appreximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge, if a well is a gas-oil of an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tesu shall be filed in triplicate within 13 days after completion of the test. Tesu shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas somes only) and gravity and GOR (oil sones only).