## MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Form C-122									
Revised	12-1-55								
<b>T</b>									

Pool	Bes	in		Formation	]	Dakets	<u> </u>		_County	Sen J	wan	
niti	al X	Special					Date of	Te <b>st</b>				
	ny Interna											
	<b>0</b> Se											
net setn	ng 42 Wt	11.6 &	9.5 T.D.	Set	t at	6768	— Per	f. 6508		То	6676	
	ng 2-3/8 Wt									То	6660	
	ay: From_											
roat	of Complet:		5 12 <b>-</b> 61	Paaka	<b>~</b>		Sing	le-Brade	nhead-G. ir Temp.	G. or	3.0. I	Oual
ate	of Complet:	ion:		racke.								
					OBS	SERVED	DATA		_			
este	ed Through	(FICE)	(Choke	e) (Neter)					Type Tap	os		
			w Data				Tubing		Casing I		1	Duration
lo.		(Choke	e) Pres	ss. Diff.	}	1	ŀ	Temp.	Press.			of Flow
	Size	Size		ig h <sub>w</sub>	o	F.	psig	°F.	psig	<sup>⊃</sup> F•		Hr.
SI							1895		1967	-	+	
2. 3.									4		<b>—</b>	
	2"	0.750	23	36		58	`		690			3 hrs
					FLOW	CALCU	JLATIONS	5			I Dada	of Flow
. [	Coeffici	ent	Pr		F.	Flow Temp. Factor		Factor	Compress. Factor		Rate of Flow Q-MCFPD	
vo.	(24-Hou	r)   <sub>7</sub>	$h_{\mathbf{w}}\mathbf{p_f}$	psia	Ft			$^{ m F}_{ m g}$	Fpv		@ 15.025 psia	
ī.												
L. 2. 3. 4. 5.	12.3650			248		.9924		9608	1.024		299▲	
<u></u>												
as L ravi	iquid Hydro ty of Liqui	id Hydro	carbons_		cf/		LCU ATI	Spec: Spec:	ific Grav ific Grav <b>1999</b>	rity Flo	owing	Fluid
丁	$P_{\mathbf{w}}$	-2	$T_{R0}$	(F <sub>c</sub> Q)	2	(F.	0)2	P <sub>w</sub> 2	P <sub>c</sub> -P <sub>v</sub>	2	Cal.	Pw
No.	Pt (psia)	P <sub>t</sub> <sup>2</sup>	F <sub>c</sub> Q	(r <sub>C</sub> / <sub>e</sub> )		(1-	Q) <sup>2</sup> e <sup>-s</sup> )	- W-			P <sub>w</sub>	P <sub>W</sub> P <sub>C</sub>
1. 2.					$ \mp$							
3.	702	<u> </u>							3503		+	1.1407
<u>4.</u> 5.			+									
Abso	olute Poten				M(	CFPD;	n <u>.75</u>	1.1	.0375			
ADDI	PANY Inte	Republ	ie Bank	Bldg. Del	les,	Terra	<b>B</b>					
AGE	NT and TITL NESSED	E	A. Dugar	, Engineer	-				C411			
	PANY					REMA	DKC	-(f)	HAFD	+-		
						T.L'.IT	11(IZO	AIT	- 10KI			
								1 48	26 1961	OW.		

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (Pw). MCF/da. @ 15.025 psia and 600 F.
- $P_c$ = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
- Pw. Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mbox{W}}\mbox{\fontsize{$\square$}}$  Differential meter pressure, inches water.
- $F_g = Gravity$  correction factor.
- $F_t$  Flowing temperature correction factor.
- $F_{DV}$  Supercompressability factor.
- n I Slope of back pressure curve.

Note: If  $P_{\mathbf{w}}$  cannot be taken because of manner of completion or condition of well, then  $P_{\mathbf{w}}$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{\mathbf{t}}$ .