NMOCC

Form 9-331a
(Feb. 1951)

Budget Bureau 42-R358.2.
Approval expires 12-31-52.

Land Office Santa Fe
Lease No. 078204-A
Unit SW/4 ~~320 Ac.~~ Sec. 33

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	X	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

RECEIVED
APR 14 1952
OIL CON. COM.
DIST. 3

March 19, 1952

Bennett-Federal Well No. 1 is located 990 ft. from {N/S} line and 990 ft. from {E/W} line of sec. 33

SW/4 33 (¼ Sec. and Sec. No.) T30N (Twp.) R10W (Range) N.M. (Meridian)

Aztec (Field) San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is * ft. *Will follow (6001' GL)

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set 100' 8-5/8" & circulated with cement. Drill to top Pictured Cliffs Sand, reduce hole and drill thru sand, run Schlumberger, ream to casing point, set 5½" on top sand w/100 sx. W.O.C. 72 hour min., drill in with cable tools, test natural, shoot w/3 QXHE per ft. Clean out & run 1" siphon string.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company THE BAY PETROLEUM CORPORATION

Address Box 957
Denver
Colorado

By Pat Lay
Pat Lay

Title Dist. Supt.