UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED
Budget Bureau No. 1004-0135
Expires:—March 31, 1993

	BUREAU OF LAND MANAGEMENT		5. LEASE DESIGNATION AND SERIAL NO.
BUNEAU OF LAND MANAGEMENT		AICIA I	
			SF-079962 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	SUNDRY NOTICES AND REP	ORTS ON WELLS	R: L.4
	Do not use this form for proposals to drill or to deepen or reentry to a different eservoir.		
,	Use "APPLICATION FOR PERMIT		
	SUBMIT IN TRIPLI	CATE (7) The same	7. 1FUNIT OR CA, AGREEMENT DESIGNATION
002			FOGELSON
١.	TYPE OF WELL		8. WELL NAME AND NO.
	OIL WELL GAS WELL OTHER :		35-1
2.	NAME OF OPERATOR		9. API WELL NO.
	CONOCO INC.		30-045-08940
3.	ADDRESS AND TELEPHONE NO.		10. FIELD AND POOL, OR EXPLORATORY AREA
_	10 DESTA DRIVE, STE. 100W, MIDLAND, T.		BASIN DAKOTA
4.	LOCATION OF WELL (Footage, Sec., T., R., M., or Survey Description) 1180' FSL - 2400' FEL, UNIT LETTER 'O-11', SEC. 35, T-30-N,R-11-W		11. COUNTY OR PARISH, STATE
			SAN JUAN COUNTY, NM
12.	CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
	TYPE OF SUBMISSION TYP		OF ACTION
		C About downersh	Chance of Plans
	Notice of Intent	Abandonment	☐ Change of Plans ☐ New Construction
	Subsequent Report	Recompletion	Non-Routine Fracturing
	Final Abandonment Notice	Plugging Back	Water Shut-Off
	That Abandoninone reduce	Casing Repair	
		Altering Casing	Conversion to Injection Dispose Water
		Other: Convert to Pumping We	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)
	 MIRU. Blow well down. ND plunger lift tree. NU BOP. Release Howco R-4 pkr @ 5000'. Tally out of hole w/ tbg string. LD pkr (pkr element not on pkr), SN, plunger spring & Mule shoe collar. Rih w/ NC, 8' x 2-3/8" pup, SN, 211 jts 2-3/8" tbg. Tagged up @ 6690'. Land EOT @ 6659' w/ SN @ 6649'. Pump 35 bbls. 1% water down tbg to insure tbg not plugged. OK. ND BOP. NU WH. Blew well to rig pit. PU & RIH rod pump, K-bars & ¾" sucker rods. Land pump in SN @ 6649'. Space pump out. Total assy run: 2": 1-¼" x 16' RHBC (6" strainer), 2 ea. 1-1/4" k-BARS, 262 ea. ¾", Grade D sucker rods, 4' x ¾" sucker rod pup, 16' x 1-½" Polish Rod (8' Polish Rod Liner) and 2' x ¾" Sucker Rod Pup (Top of Polish Rod). NU pumping tee equip. Load tbg w/ 1% KCI water and verify pump was landed. Function stroke pump. OK. 		
			DEGETVED OCT 2 1 1997
			OIL CON. DIV.
14. I hereby certify that the toregoing is true and correct SIGNED TITLE DEBRA BEMENDERFER, As agent for Conoco Inc. DATE 10-09-97			
	(This space for Federal or State office use) APPROVED BY Conditions of approval, if any:	TITLE	ACCEPTED FOR RECORD
			OCT 1 6 1997
Ti	tle 18 U.S.C. Section 1001, makes it a crime for any pers titious or fraudulent statements or representations as to a	on knowingly and willfully to make to any depar any matter within its jurisdiction.	tment or agency of the Unites States any false,