


(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

	Bu Ap	dget prov	Bureau al expir	42-R35 es 12-31-	8.3. -55.
Land Offic	ce				
Lease No.	BX	Ø,	250		
Timi+					

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.
IOTICE OF INTENTION TO TEST WATER SHUT-OFF	
OTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.
OTICE OF INTENTION TO THE STATE OF THE STATE	SUBSEQUENT REPORT OF ABANDONMENT
OTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
OTICE OF INTENTION TO ABANDON WELL	
(INDICATE ABOVE BY CHECK MA	ARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	November 2# 19 ⁵⁵
Total Paderal	15
ll No is located _1660. ft. fro	om. S line and ft. from line of sec.
(Twp.)	(Range) (Meridian)
(1/2 Sec. and Sec. No.)	Jew Mexico
Field) (Coun	nty or Subdivision) (State or Territory)
e names of and expected dopons to objective contact, and a	v sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemen all other important proposed work)
nig points, and	ig. Fulled tabing, classed out small amount od with 600 bile water, 45 BBS rate. Frenkished with 75 bbls water.
CAVINGS. On Gotober 20, 1986.	ig. Fulled tabing, classed out small meant
THAC ECREOTER, October 30, 1985. Hoved in cable tool ricevings. On Getaber Slat, fraces 1200%. Treated at 850% Used 30,	ig. Fulled tabing, classed out small assount od with 400 bile water, 48 88% rate. Sreaked with 75 bile unter.
PRAC ECRECYCE: October 20, 1985. Hoved in cable tool ricevings. On October Slat. fraces 1200%. Treated at 850%. Used 20, Reren tubing. 25	ic. Fulled tabing, classed out small meant of with 400 bble water, 45 SSS rate. Sreaked ,000 f fine sand flushed with 75 bble mater. 40° tubing in hole. 2° to 2577°, ID.
PRAC MCHEOTER: October 30, 1986. Hered in cable tool rice cavings. On October 31st, fraces 1290%. Treated at 850%. Beed 30, Reren tubing. 256 Enterval treated, 346 Ave. daily prod. October 1956 Unifected production after for	ic. Fulled tabing, classed out small meant of with 400 bble water, 45 SSS rate. Sreaked ,000 f fine sand flushed with 75 bble mater. 40° tubing in hole. 2° to 2577°, ID.
myed in cable tool ricevings. In Getaber Slat, fraces 1200. Trented at 350% Used 35. Reren tubing. 356 Interval treated, 346 This set of process of a first fraces approve	with 600 bale water, 45 SEE rate. Breaked out small executed with 600 bale water, 45 SEE rate. Breaked 000 from small flushed with 75 bbls water. 10° tubing in hole. 20° tubing in hole.
PRAC MCHEOTER: October 30, 1986. Hered in cable tool rice cavings. On October 31st, fraces 1290%. Treated at 850%. Beed 30, Reren tubing. 256 Enterval treated, 346 Ave. daily prod. October 1956 Unifected production after for	with 600 bale water, 45 SEE rate. Breaked out small executed with 600 bale water, 45 SEE rate. Breaked 000 from small flushed with 75 bbls water. 10° tubing in hole. 20° tubing in hole.
reactions of the series of the	with 600 bale water, 45 SEE rate. Breaked out small executed with 600 bale water, 45 SEE rate. Breaked 000 from small flushed with 75 bbls water. 10° tubing in hole. 20° tubing in hole.



Reference to the second second