Form 9-881 a (Feb. 1951)



## (SUBMIT IN TRIPLICATE)

## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	Sen no	
Lease No	07821	4
	Can The	T-30N-9-13W

Unit S/2 Sec 3h, T-30N, R-13W, N.M.P.M., San Juan County, New Mexico

GPO 9 18 507

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	1 0	
NOTICE OF INTENTION TO DRILL		TER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLAN		OOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER	i II	
NOTICE OF INTENTION TO RE-DRILL OR	REPAIR WELL SUBSEQUENT REPORT OF RE-	-DRILLING OF PEPER
NOTICE OF INTENTION TO SHOOT OR AC	IDIZE SUBSEQUENT REPORT OF ABA	ANDONMENT THE
NOTICE OF INTENTION TO PULL OR ALT	R CASING SUPPLEMENTARY WELL HISTO	ORY
NOTICE OF INTENTION TO ABANDON WE	<b>_</b>	
(	LBOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OT	THER DATA)
(INDICATE	BOVE BY CHECK MARK RATURE OF REPORT, NOTICE, OR O.	Carried Author
	Oct	ober 9 U
Well No. 2 <u>Eccord</u> is located	1850ft. from S line and 1190 ft.	from W line of sec. 34
Na/A SWA 34 (14 Sec. No.)	30M 13n N.M.P. (Twp.) (Range) (Meridian	
<b>V-</b>	San Juan	New Maxico
Wildest (Field)	(County or Subdivision)	(State or Territory)
	. I de des fi	OC. F. J. 9 1959
The elevation of the derrick fl	oor above sea level is _5632_ ft.	OIL CON. COM
	DETAILS OF WORK	DIST. 3
	DETAILS OF WORK	Diarra
(State names of and expected depths to ob	DEIAILS OF WORK jective sands; show sizes, weights, and lengths of propose ing points, and all other important proposed work)	d casings; indicate mudding jobs, coment-
1. Ran 202 jts. han, h 63h7' R.K.B. Cmtd. 2. Perf. h shots/ft. 6 and 31,110 gals. W 3. Set Guiberson bridg	ing points, and all other important proposed work)  .50#, J-55, casing on August 25, w/425 sx regular cement with 4% 286-6306; 6260-6286; Sand-water ter on August 30, 1959. e plug at 6250'. Perf. h snots/ 000# sand and 32,736 gals. water . 4.7#, J-55 tubing on September	1959. Pipe landed @ gel. frac using 30,000# sand
1. Ran 202 jts. hhm, h 63h7' R.K.B. Cmtd. 2. Perf. h shots/ft. 6 and 31,110 gals. w 3. Set Guiberson bridg water frac with 30; h. Ran 205 jts. 2-3/8' landed at 6106.89'  I understand that this plan of work n	jective sands; show sizes, weights, and lengths of proposed ing points, and all other important proposed work)  .50#, J-55, casing on August 25, w/425 sx regular cement with 4% 286-6306; 6260-6286; Sand-water ter on August 30, 1959.  ter on August 30, 1959.  te plug at 6250'. Perf. it snots/000# sand and 32,736 gals. water, it.7#, J-55 tubing on September R.K.B.	1959. Pipe landed @ gel. frac using 30,000# sand ft. 6228-6116. Sand-con August 31, 1959.