

N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

AREA 640 ACRES
LOCATE WELL CORRECTLY

CARROLL & HANNETTS

BOX 353- FARMINGTON, NEW MEXICO.

Company or Operator

Address

OLLIE MAE CARROLL

Well No.

2

in NE 1/4 Sec.

33

T. 30N

R. 12 W

N. M. P. M.

Fuleher Basin

Field,

San Juan

County.

Well is 2320

feet south of the North line and

330

feet west of the East line of

Sec 33

If State land the oil and gas lease is No.

No

Assignment No.

If patented land the owner is

Ollie Mae Carroll

Address

Box 353, Farmington, N.M.

If Government land the permittee is

Address

The Lessee is

Carroll and Hannetts'

Address

Box 353, Farmington, N.M.

Drilling commenced

April

19

Drilling was completed

June

19

Name of drilling contractor

C.W. Carroll

Address

Box 353, Farmington, N.M.

Elevation above sea level at top of casing

5773

feet.

The information given is to be kept confidential until

19

OIL SANDS OR ZONES

No. 1, from 390

to 900-01140

No. 4, from

to

No. 2, from 1550

to 1610-G

No. 5, from

to

No. 3, from 1824

to 1930 P.O.G.

No. 6, from

to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 160

to 275-377

feet.

2 barrels per hour.

No. 2, from 980

to 987

feet.

4 " " " "

No. 3, from 1302

to 1814

feet.

water

No. 4, from

to

feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
15 1/2	60	8		60'					S.S.
12 1/2	50	8		487'-9"					
10	45	8		610'-10"					
8 1/2	32	8		1520'					
7" O.D.	20	8		1824'					

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
8 1/2	7" O.D.	1824'	25	Halliburton		

PLUGS AND ADAPTERS

Heaving plug—Material

Length

Depth Set

Adapters—Material

Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from Spudder feet to feet, and from feet to feet

PRODUCTION

Put to producing Not Yet on the line 19 (July 2, 1946)

The production of the first 24 hours was barrels of fluid of which % was oil; %

emulsion; % water; and % sediment. Gravity, Be

If gas well, cu. ft. per 24 hours 1,500,000 Gallons gasoline per 1,000 cu. ft. of gas

Rock pressure, lbs. per sq. in. 525

EMPLOYEES

Bill Powell, Driller

Clay Gode, Driller C.W. Carroll, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 9th

day of July 19 46

Ruby Hicks
Notary Public

My Commission expires May 27, 1950

Place Date

Name C.W. Carroll

Position

Representing

Company or Operator

Address

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	40	40	Boulders
40	80	40	Sandstone.
80	130	50	Sand.
130	140	10	Sandstone.
140	160	20	Dark Shale.
160	275	115	Grey Sand- 2 Bailers of water.
275	370	95	Gray Shale.
370	377	7	Sand- Increase in water.
377	405	28	Sandy Shale.
405	503	98	Grey Sand.
503	525	22	Grey Sandy Shale.
525	555	30	Blue Shale and Lime.
555	890	335	Grey Sandy Shale.
890	900	10	Sand- Showing of Oil and Gas.
9900	930	30	Sand.
930	980	50	Hard Sandy Shale.
980	1005	25	Water Sand. Increase from 980 to 987.
1005	1505	500	Sandy Shale.
1505	1515	10	Dark Shale and Coal.
1515	1530	15	Dark Shale.
1530	1550	20	Grey Shale.
1550	1610	60	Dark Shale- Gas Show.
1610	1635	25	Gray Shale.
1635	1670	35	Dark Shale.
1670	1735	65	Grey Shale.
1735	1780	45	Hard Shale.
1780	1802	22	Coal
1802	1814	12	Shale and Coal.
1814	1824	10	Top of Picture Cliff Sand.
1824	1936	106	Picture Cliff Sand.
1930	1936	6	Shale.