UNITED STATES

DEPARTMENT OF THE INTERIOR BURRAU OF LAND MANAGEMENT

Sundry Notices ar	nd Reports on Wells 20 00 2: 76
	5. Lease Number SF-043260-B
. Type of Well	6. If Indian, All. or Tribe Name
GAS	Tribe Name
	7. Unit Agreement Nam
. Name of Operator	P 2000
BURLINGTON RESOURCES ON 1 CM	E OLOGNED N
RESOURCES OIL & GAS	COMPANY 0/87 3 8. Well Name & Number
. Address & Phone No. of Operator	Murphy E #2
PO Box 4289, Farmington, NM 8749	9 (505) 32 (610) 6 8 9. API Well No.
	30-045-09060
. Location of Well, Footage, Sec., T	, R, M 10. Field and Pool
990'FNL, 1550'FWL, Sec.34, T-30-N,	R-11-W, NMPM Aztec Pict'd Cliff 11. County and State San Juan Co, NM
Type of Submission Notice of Intent X Subsequent Report	NATURE OF NOTICE, REPORT, OTHER DATA Type of Action Abandonment Change of Plans Recompletion New Construction Plugging Back Non-Routine Fracturing Casing Repair Water Shut off
Final Abandonment	Altering Casing Conversion to Injection Other - Restimulation
Final AbandonmentX_	Altering Casing Conversion to Injection Other - Restimulation
Final Abandonment _X Describe Proposed or Completed	Altering Casing Conversion to Injection Other - Restimulation Operations
Final Abandonment _X 3. Describe Proposed or Completed 5-31-00 MIRU. ND WH. NU BOP. T	Altering Casing Conversion to Injection Other - Restimulation Operations TOOH w/1" tbg. SDON.
Final Abandonment X 3. Describe Proposed or Completed 5-31-00 MIRU. ND WH. NU BOP. T 6-1-00 TIH w/bit, tag up @ 21 6-2-00 Blow well. TOOH w/bit.	Altering Casing Conversion to Injection Other - Restimulation Operations TOOH w/1" tbg. SDON. 197'. Drill out to 2336'. Circ hole clean. SDON. TIH w/77 jts 2 7/8" 6.4# J-55 csg, set @ 2336'.
Final Abandonment X 3. Describe Proposed or Completed 5-31-00 MIRU. ND WH. NU BOP. To the second	Altering Casing Conversion to Injection Other - Restimulation Operations TOOH w/1" tbg. SDON. 197'. Drill out to 2336'. Circ hole clean. SDON. TIH w/77 jts 2 7/8" 6.4# J-55 csg, set @ 2336'. S "B" cmt w/2% econolite, 5 pps gilsonite, 0.25 pps
Final Abandonment X 3. Describe Proposed or Completed 5-31-00 MIRU. ND WH. NU BOP. T 6-1-00 TIH w/bit, tag up @ 21 6-2-00 Blow well. TOOH w/bit. Cmtd w/125 sx Class flocele (258 cu ft)	Altering Casing Conversion to Injection Other - Restimulation Operations TOOH w/1" tbg. SDON. 197'. Drill out to 2336'. Circ hole clean. SDON. 197' TIH w/77 jts 2 7/8" 6.4# J-55 csg, set @ 2336'. 18 "B" cmt w/2% econolite, 5 pps gilsonite, 0.25 pps 10 Tail w/25 sx Class "B" cmt w/1% econolite, 0.25 pps
Final Abandonment X Describe Proposed or Completed 5-31-00 MIRU. ND WH. NU BOP. To the second of	Altering Casing Conversion to Injection Other - Restimulation Operations TOOH w/1" tbg. SDON. 197'. Drill out to 2336'. Circ hole clean. SDON. TIH w/77 jts 2 7/8" 6.4# J-55 csg, set @ 2336'. S "B" cmt w/2% econolite, 5 pps gilsonite, 0.25 pps
Final Abandonment X 3. Describe Proposed or Completed 5-31-00 MIRU. ND WH. NU BOP. To the second of the second	Altering Casing Conversion to Injection Other - Restimulation Operations TOOH w/1" tbg. SDON. 197'. Drill out to 2336'. Circ hole clean. SDON. TIH w/77 jts 2 7/8" 6.4# J-55 csg, set @ 2336'. S "B" cmt w/2% econolite, 5 pps gilsonite, 0.25 pps O. Tail w/25 sx Class "B" cmt w/1% econolite, 0.25 ps Sonite (37 cu ft). Circ 8 bbl cmt to surface. RD. Reserved.
Final Abandonment X 3. Describe Proposed or Completed 5-31-00 MIRU. ND WH. NU BOP. To the second of the second	Altering Casing Conversion to Injection Other - Restimulation Operations FOOH w/1" tbg. SDON. 197'. Drill out to 2336'. Circ hole clean. SDON. 197' TIH w/77 jts 2 7/8" 6.4# J-55 csg, set @ 2336'. 198" cmt w/2% econolite, 5 pps gilsonite, 0.25 pps 10. Tail w/25 sx Class "B" cmt w/1% econolite, 0.25 pps 10. Tail w/25 sx Class "B" cmt w/1% econolite, 0.25 pps 11. Sonite (37 cu ft). Circ 8 bbl cmt to surface. RD. Response & 2 7/8" csg to 5000 psi, OK. Perf PC formation 12. Special control of the control of th
Final Abandonment X 3. Describe Proposed or Completed 5-31-00 MIRU. ND WH. NU BOP. T 6-1-00 TIH w/bit, tag up @ 21 6-2-00 Blow well. TOOH w/bit. Cmtd w/125 sx Class flocele (258 cu ft) flocele, 5 pps gils released. 6-7-00 RU. PT lines to 6000 p @ 2193, 2195, 2199, 2243, 2247, 2251, 2	Altering Casing Conversion to Injection Other - Restimulation Operations TOOH w/1" tbg. SDON. 197'. Drill out to 2336'. Circ hole clean. SDON. TIH w/77 jts 2 7/8" 6.4# J-55 csg, set @ 2336'. S "B" cmt w/2% econolite, 5 pps gilsonite, 0.25 pps Tail w/25 sx Class "B" cmt w/1% econolite, 0.25 ps Sonite (37 cu ft). Circ 8 bbl cmt to surface. RD. R: Osi & 2 7/8" csg to 5000 psi, OK. Perf PC formation 205, 2207, 2212, 2219, 2223, 2233, 2237, 2240, 2254' w/15 0.24" diameter holes. Brk dwn perfs.
Final Abandonment	Altering Casing Conversion to Injection Other - Restimulation Operations TOOH w/1" tbg. SDON. 197'. Drill out to 2336'. Circ hole clean. SDON. TIH w/77 jts 2 7/8" 6.4# J-55 csg, set @ 2336'. S "B" cmt w/2% econolite, 5 pps gilsonite, 0.25 pps Tail w/25 sx Class "B" cmt w/1% econolite, 0.25 ps Sonite (37 cu ft). Circ 8 bbl cmt to surface. RD. Respectively. OSI & 2 7/8" csg to 5000 psi, OK. Perf PC formation, 2205, 2207, 2212, 2219, 2223, 2233, 2237, 2240, 2254' w/15 0.24" diameter holes. Brk dwn perfs. OK. Frac PC w/422 bbl 30# lnr gel, 178,000# 20/40
Final Abandonment	Altering Casing Conversion to Injection Other - Restimulation Operations TOOH w/1" tbg. SDON. 197'. Drill out to 2336'. Circ hole clean. SDON. 197'. TIH w/77 jts 2 7/8" 6.4# J-55 csg, set @ 2336'. 18 "B" cmt w/2% econolite, 5 pps gilsonite, 0.25 pps 10. Tail w/25 sx Class "B" cmt w/1% econolite, 0.25 ps 10. Tail w/25 sx Class "B" cmt
Final Abandonment	Altering Casing Conversion to Injection Other - Restimulation Operations TOOH w/1" tbg. SDON. 197'. Drill out to 2336'. Circ hole clean. SDON. TIH w/77 jts 2 7/8" 6.4# J-55 csg, set @ 2336'. S "B" cmt w/2% econolite, 5 pps gilsonite, 0.25 pps Tail w/25 sx Class "B" cmt w/1% econolite, 0.25 ps Sonite (37 cu ft). Circ 8 bbl cmt to surface. RD. Respectively. OSI & 2 7/8" csg to 5000 psi, OK. Perf PC formation, 2205, 2207, 2212, 2219, 2223, 2233, 2237, 2240, 2254' w/15 0.24" diameter holes. Brk dwn perfs. OK. Frac PC w/422 bbl 30# lnr gel, 178,000# 20/40
Final Abandonment	Altering Casing Conversion to Injection Other - Restimulation Operations TOOH w/1" tbg. SDON. 197'. Drill out to 2336'. Circ hole clean. SDON. 197'. TIH w/77 jts 2 7/8" 6.4# J-55 csg, set @ 2336'. 18 "B" cmt w/2% econolite, 5 pps gilsonite, 0.25 pps 10. Tail w/25 sx Class "B" cmt w/1% econolite, 0.25 ps 10. Tail w/25 sx Class "B" cmt
Final Abandonment	Altering Casing Conversion to Injection Other - Restimulation Operations TOOH w/1" tbg. SDON. 197'. Drill out to 2336'. Circ hole clean. SDON. 197' Till w/77 jts 2 7/8" 6.4# J-55 csg, set @ 2336'. 198" cmt w/2% econolite, 5 pps gilsonite, 0.25 pps 10. Tail w/25 sx Class "B" cmt w/1% econolite, 0.25 pps
Final Abandonment X 3. Describe Proposed or Completed 5-31-00 MIRU. ND WH. NU BOP. To 6-1-00 TIH w/bit, tag up @ 21 6-2-00 Blow well. TOOH w/bit. Cmtd w/125 sx Class flocele (258 cu ft) flocele, 5 pps gils released. 6-7-00 RU. PT lines to 6000 psi, 2193, 2195, 2199, 2243, 2247, 2251, 26-8-00 PT lines to 6000 psi, AZ sand, 421,700 Sc 6-9/11-00 Flow back well. ND from 14. I hereby certify that the forest	Altering Casing Conversion to Injection Other - Restimulation Operations TOOH w/1" tbg. SDON. 197'. Drill out to 2336'. Circ hole clean. SDON. 197' Till w/77 jts 2 7/8" 6.4# J-55 csg, set @ 2336'. 198" cmt w/2% econolite, 5 pps gilsonite, 0.25 pps 10. Tail w/25 sx Class "B" cmt w/1% econolite, 0.25 pps
	Altering Casing Conversion to Injection Other - Restimulation Operations TOOH w/1" tbg. SDON. 197'. Drill out to 2336'. Circ hole clean. SDON. 197'. Drill out to 2336'. Secondary

SWY STATE V