HAUTED STATES

5.	LEASE F.O.	68990	_

DEPARTMENT OF THE INTERIOR	6. IF INDIÁN, ALLOTTEE OR TRIBE NAME		
GEOLOGICAL SURVEY			
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME		
Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)			
1. oil G gas G	Iludson E		
well well well other	9. WELL NO.		
2. NAME OF OPERATOR Tenneco Oil Company	10. FIELD OR WILDCAT NAME		
3. ADDRESS OF OPERATOR	Fulcher Kutz		
Box 3249, Englewood, Co 80155	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA		
below.)	Sec 33, T30N, R12W 12. COUNTY OR PARISH 13. STATE		
AT SURFACE 480' FSL, 800' FEL AT TOP PROD. INTERVAL:	<u> </u>		
AT TOTAL DEPTH:	San Juan New Mexico 14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,			
REPORT, OR OTHER DATA	-15 ELEVATIONS (SHOW DF, KDB, AND WD)		
	<u>5729' кв</u>		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	<i>)</i> \		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF THE PROPERTY OF	(NOTE: Report results of multiple completion or zone change on Form 9-330.)		
FRACTURE TREAT SHOOT OR ACIDIZE), /		
DEDAID WELL	(NOTE: Report results of multiple completion or zone		
PULL OR ALTER CASING TO THE	change on Form 9-330.)		
MULTIPLE COMPLETE			
PULL OR ALTER CASING HPR H	•		
(other)			
	As all postinent details, and give pertinent dates		
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta	directionally drilled, give subsurface locations and		

including estimated date of starting any proposed work. If well is directionally drilled, gi measured and true vertical depths for all markers and zones pertinent to this work.)*

4/14/81 Rig up service unit. Pumped into well @ 3 BPM. POOH w/ 14" tbg. Removed Larkin head. RD move off service unit. Pumped 115sx Class B cmt down 3½" csg. Pumped 16sx down 7" csg. Pumped 40 sx down outside of 7" csg. Cut off well head. Install P & A marker. Well is plugged and abandoned.

Subsurface Safety Valve: Manu, and Type			AUG 2 7 1987 OIL CON. DIV. 1 Set DIST. 3
Subsurface Safety Valve: Manu. and Type	<i>1</i> 2		
18. I hereby certify that the foregoing is to SIGNED Carley Watkins	THE Asst. Div. Adm. Mgr.	DATE _E	April 15, 1981
	(This space for Federal or State office use)		
APPROVED BY	TITLE	DATE_	APPROVED AS AMENDE
to plugging of the well bore	•		
nder bond is retained until			JAN 118 1985
toration is completed.	*See Instructions on Reverse Side		alu HMda
1WK 1-22-85 BC	EADAMAGECTA OODV		1 MILLENBACH

Approved as Liability u surface res

FARMIMETEM COPY